

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV2205B

SIMOTICS XP - 200 L - IM B5 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data II 3G Ex ec IIC T3 Gc
-/-

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
DOL duty (S1) - 155(F) to 130(B)																	
380	Δ	50	30.00	-/-	59.00	1470	195.0	92.3	92.8	92.5	0.84	0.80	0.71	6.7	2.5	3.7	IE2
660	Y	50	30.00	-/-	34.00	1470	195.0	92.3	92.8	92.5	0.84	0.80	0.71	6.7	2.5	3.7	IE2
440	Δ	60	34.50	-/-	57.00	1770	186.0	93.0	93.4	93.1	0.85	0.82	0.74	7.2	2.7	3.2	IE2
440	Δ	60	30.00	-/-	50.00	1778	161.0	93.0	93.1	92.2	0.84	0.79	0.70	8.2	3.2	3.7	IE2
IM B5 / IM 3001		FS 200 L				IP55			IEC/EN 60034		IEC, DIN, ISO, VDE, EN						
Environmental conditions : -20 °C - +40 °C / 1000 m									Locked rotor time (hot / cold) : 18 s 31.5 s								

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	70 / 77 dB(A) ^{2) 3)}	72 / 79 dB(A) ^{2) 3)}	Vibration severity grade	A
Moment of inertia	0.2000 kg m ²		Thermal class	F
Bearing DE NDE	6212 2Z C3	6212 2Z C3	Duty type	S1
bearing lifetime			Direction of rotation	bidirectional
L _{10mh} F _{Rad min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Frame material	cast iron
Regreasing device	Without		Net weight of the motor (IM B3)	230 kg
Grease nipple	-/-		Coating (paint finish)	Standard paint finish C2
Type of bearing	Locating bearing NDE		Color, paint shade	RAL7030
Condensate drainage holes	With (standard)		Motor protection	(B) 3 PTC thermistors - for tripping (2 terminals)
External earthing terminal	With (standard)		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	35 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	27 mm - 35 mm
Type of terminal box	TB1 L01	Cable entry	2xM50x1,5-2xM20x1,5
Contact screw thread	M6		

Notes:
I_A/I_N = locked rotor current / current nominal
M_K/M_N = locked rotor torque / torque nominal
M_K/M_N = break down torque / nominal torque
1) L_{10mh} according to DIN ISO 281 10/2010
2) at rated power / at full load
3) Value is valid only for DOL operation with motor design IC411

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
IN LVM		SPC					
	document type	datasheet			document status	released	
	title	1MB1531-2AB53-3FB4-Z B02+D37+M10+Q02			document number		
© INNOMOTICS 2023		rev.	creation date	language	Page		
		951	2023-12-14	en	1/2		

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV2205B

SIMOTICS XP - 200 L - IM B5 - 4p

Special design

B02	Acceptance test certificate 3.1 acc. to EN 10204	M10	Additional rating plate, loose
D37	IECEx-certification	Q02	Anti-condensation heating for 230 V (2 terminals)

Additional information:

Space heaters

Technical data: 1-phase, 230 V 52W

Notes:

responsible dep. IN LVM	technical reference	created by SPC	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
SIEMENS	document type datasheet			document status released			
	title 1MB1531-2AB53-3FB4-Z			document number			
© INNOMOTICS 2023	B02+D37+M10+Q02			rev. 951	creation date 2023-12-14	language en	Page 2/2