

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3072B

SIMOTICS XP - 71 M - IM V1 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data	II 3G Ex ec IIC T3 Gc -/-
-----------------	------------------------------

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
DOL duty (S1) - 155(F) to 130(B)																	
230	Δ	50	0.25	-/-	1.19	1395	1.7	73.5	73.7	70.4	0.72	0.63	0.50	4.2	2.5	2.6	IE3
400	Y	50	0.25	-/-	0.68	1395	1.7	73.5	73.7	70.4	0.72	0.63	0.50	4.2	2.5	2.6	IE3
460	Y	60	0.29	-/-	0.69	1695	1.6	73.4	73.3	70.0	0.72	0.63	0.51	4.5	2.5	2.6	IE3
460	Y	60	0.25	-/-	0.63	1715	1.4	73.4	72.3	68.0	0.68	0.59	0.47	4.9	2.9	3.1	IE3
IM V1 / IM 3011		FS 71 M				IP55			IEC/EN 60034		IEC, DIN, ISO, VDE, EN						
Environmental conditions : -20 °C - +40 °C / 1,000 m									Locked rotor time (hot / cold) : 53.5 s 61.9 s								

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	44 / 55 dB(A) ^{2) 3)}	47 / 58 dB(A) ^{2) 3)}	Vibration severity grade	A
Moment of inertia	0.0009 kg m ²		Thermal class	F
Bearing DE NDE	6202 2Z C3	6202 2Z C3	Duty type	S1
bearing lifetime			Direction of rotation	bidirectional
L _{10mh} F _{Rad min} for coupling operation 50 60Hz ¹⁾	20000 h	16000 h	Frame material	cast iron
Regreasing device	Without		Net weight of the motor (IM B3)	13 kg
Grease nipple	-/-		Coating (paint finish)	Standard paint finish C2
Type of bearing	Preloaded bearing DE		Color, paint shade	RAL7030
Condensate drainage holes	Without		Motor protection	(A) without (Standard)
External earthing terminal	With (standard)		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	4 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	9 mm - 17 mm
Type of terminal box	TB1 D01	Cable entry	1xM25x1,5
Contact screw thread	M4		

Notes:

I_A/I_N = locked rotor current / current nominal
M_K/M_N = locked rotor torque / torque nominal
M_K/M_N = break down torque / nominal torque

1) L_{10mh} according to DIN ISO 281 10/2010
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
IN LVM		SPC					
SIEMENS	document type				document status		
	datasheet				released		
	title				document number		
	1MB1533-0CB22-2GA4-Z						
© INNOMOTICS 2023	H00				rev.	creation date	language
					951	2023-12-14	en
				Page	1/2		

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3072B

SIMOTICS XP - 71 M - IM V1 - 4p

Special design

H00 Canopy

Notes:

responsible dep. IN LVM	technical reference	created by SPC	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.	Link documents
	document type datasheet				document status released
	title 1MB1533-0CB22-2GA4-Z				document number
© INNOMOTICS 2023	H00	rev. 951	creation date 2023-12-14	language en	Page 2/2

