

XP motor type: 1CV3090B low-voltage motor, IEC squirrel-cage rotor, self-cooled, IP55 temperature class 155(F) according to 130(B) gray cast iron housing Basic Line Premium Efficiency IE3, 4-pole * size 90s * 1.1 kW (50 Hz), 1.27 kW (60 Hz) Ex ec IIC T3 Gc version for zone 2 according to IEC/EN 60 079-7 standard color RAL 7030 if no order code is specified for selecting another color. Purchase of this product is exclusively governed by the Innomatics T&Cs located at <https://www.innomotics.com/terms-and-conditions> Non-standard winding 3 AC..Hz,...V,...kW IM B3 without motor protection Terminal box at top B92=Dokumentation package "Projects" C02=VIK version D37=IECEX certification D70=MEPS Australia H07=Stainless screws (external) H22=Degree of protection IP56 L07=Smooth running of the shaft extension according to IEC 60072-1 precision class N06=Temperature class 155 (F), utilized according to 130(B), Coolant temperature 50°, derating approx. 8% N31=Increased humidity/temp. with 60 to 100 g water per m3 air S04=Special paint finish offshore S05=Internal coating Y53=Paint finish in other standard RAL colors (for selection see catalog) RAL.. Y80=Additional rating plate with deviating rating plate data

Further information

Industry Online Support (Manuals, Catalogs, Certificates, FAQ, ...)
<https://support.industry.siemens.com/cs/products?mfn=ps&lc=en-WW>
Industry Mall (Online ordering system)
<https://mall.industry.siemens.com>

