

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3164B

SIMOTICS XP - 160 L - IM B3 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data II 3G Ex ec IIC T3 Gc
-/-

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
DOL duty (S1) - 155(F) to 130(B)																	
400	Δ	50	15.00	-/-	28.50	1465	98.0	92.1	92.7	92.0	0.83	0.78	0.67	7.9	2.8	3.4	IE3
690	Y	50	15.00	-/-	16.40	1465	98.0	92.1	92.7	92.0	0.83	0.78	0.67	7.9	2.8	3.4	IE3
460	Δ	60	17.30	-/-	28.50	1765	94.0	92.4	92.5	92.0	0.83	0.79	0.69	7.9	2.7	3.3	IE2
460	Δ	60	15.00	-/-	25.00	1775	81.0	93.0	92.9	92.1	0.81	0.75	0.64	8.9	3.1	3.8	IE3
IM B3 / IM 1001		FS 160 L				IP55			IEC/EN 60034		IEC, DIN, ISO, VDE, EN						
Environmental conditions : -20 °C - +40 °C / 1000 m									Locked rotor time (hot / cold) : 24.6 s 33.3 s								

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	58 / 66 dB(A) ^{2) 3)}	66 / 74 dB(A) ^{2) 3)}	Vibration severity grade	A
Moment of inertia	0.0890 kg m ²		Thermal class	F
Bearing DE NDE	6209 2Z C3	6209 2Z C3	Duty type	S1
bearing lifetime			Direction of rotation	bidirectional
L _{10mh} F _{Rad min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Frame material	cast iron
Regreasing device	Without		Net weight of the motor (IM B3)	133 kg
Grease nipple	-/-		Coating (paint finish)	Standard paint finish C2
Type of bearing	Locating bearing NDE		Color, paint shade	RAL7030
Condensate drainage holes	With (standard)		Motor protection	(B) 3 PTC thermistors - for tripping (2 terminals)
External earthing terminal	With (standard)		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	16 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	19 mm - 28 mm
Type of terminal box	TB1 J01	Cable entry	2xM40x1,5-2xM16x1,5
Contact screw thread	M5		

Notes:
I_A/I_N = locked rotor current / current nominal
M_K/M_N = locked rotor torque / torque nominal
M_K/M_N = break down torque / nominal torque
1) L_{10mh} according to DIN ISO 281 10/2010
2) at rated power / at full load
3) Value is valid only for DOL operation with motor design IC411

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
IN LVM		SPC					
	document type	datasheet			document status		
					released		
	title	1MB1533-1DB43-4AB4-Z			document number		
© INNOMOTICS 2024	B02	rev.	creation date		language	Page	
		953	2024-01-11		en	1/2	

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3164B

SIMOTICS XP - 160 L - IM B3 - 4p

Special design

B02 Acceptance test certificate 3.1 acc. to EN 10204

Notes:

responsible dep. IN LVM	technical reference	created by SPC	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
	document type datasheet			document status released			
	title 1MB1533-1DB43-4AB4-Z			document number			
© INNOMOTICS 2024	B02			rev. 953	creation date 2024-01-11	language en	Page 2/2