

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3182B SIMOTICS XP - 180 M - IM V5 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data II 3G Ex ec IIC T3 Gc
-/-

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
DOL duty (S1) - 155(F) to 130(B)																	
400	Δ	50	16.09	-/-	31.50	1470	104.5	92.9	93.1	92.9	0.79	0.73	0.62	8.3	2.9	3.8	IE3
690	Y	50	16.09	-/-	18.30	1470	104.5	92.9	93.1	92.9	0.79	0.73	0.62	8.3	2.9	3.8	IE3
460	Δ	60	18.53	-/-	31.00	1770	100.0	93.8	93.9	93.6	0.80	0.74	0.64	8.3	2.8	3.7	IE3
460	Δ	60	18.50	-/-	30.50	1775	100.0	93.6	93.7	93.1	0.81	0.75	0.64	7.8	2.7	3.6	IE3
IM V5 / IM 1011			FS 180 M				IP55			IEC/EN 60034		IEC, DIN, ISO, VDE, EN					
Environmental conditions : -20 °C - +55 °C / 1,000 m									Locked rotor time (hot / cold) : 28.7 s 41.6 s								
These values are calculated. The final rating plate data will be calculated when the order is placed																	
The efficiency values and efficiency class according to EuP directive are valid for standard power ratings under standard conditions.																	

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	66 / 73 dB(A) ^{2) 3)}	68 / 75 dB(A) ^{2) 3)}	Vibration severity grade	A
Moment of inertia	0.1300 kg m ²		Thermal class	F
Bearing DE NDE	6210 2Z C3	6210 2Z C3	Duty type	S1
bearing lifetime			Direction of rotation	bidirectional
L _{10mh} F _{Rad min} for coupling operation 50 60Hz ¹⁾	20000 h	16000 h	Frame material	cast iron
Regreasing device	Without		Net weight of the motor (IM B3)	165 kg
Grease nipple	-/-		Coating (paint finish)	Standard paint finish C2
Type of bearing	Locating bearing NDE		Color, paint shade	RAL7030
Condensate drainage holes	With (standard)		Motor protection	(A) without (Standard)
External earthing terminal	With (standard)		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	16 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	19 mm - 28 mm
Type of terminal box	TB1 J01	Cable entry	2xM40x1,5
Contact screw thread	M5		

Notes:
I_A/I_N = locked rotor current / current nominal
M_A/M_N = locked rotor torque / torque nominal
M_K/M_N = break down torque / nominal torque
1) L_{10mh} according to DIN ISO 281 10/2010
2) at rated power / at full load
3) Value is valid only for DOL operation with motor design IC411

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.	Link documents
IN LVM		SPC			
SIEMENS	document type				document status
	datasheet				released
	title				document number
	1MB1533-1EB23-4CA4-Z				
© INNOMOTICS 2023	H00+N07				rev.
					951
		creation date		language	Page
		2023-12-14		en	1/2

SIMOTICS XP - 180 M - IM V5 - 4p

Notes:

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
IN LVM		SPC					
	document type			document status			
	datasheet			released			
	title			document number			
	1MB1533-1EB23-4CA4-Z						
	H00+N07			rev.	creation date	language	Page
© INNOMOTICS 2023				951	2023-12-14	en	2/2