

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3220B

SIMOTICS XP - 225 S - IM V6 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project
Remarks		

II 3G Ex ec IIC T3 Gc																	
-/-																	
Electrical data																	
U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
DOL duty (S1) - 155(F) to 130(B)																	
400	Δ	50	37.00	-/-	66.00	1478	240.0	93.9	94.5	94.4	0.86	0.83	0.74	6,4	2.5	2.7	IE3
690	Y	50	37.00	-/-	38.50	1478	240.0	93.9	94.5	94.4	0.86	0.83	0.74	6,4	2.5	2.7	IE3
460	Δ	60	42.50	-/-	66.00	1778	230.0	93.6	94.1	93.9	0.86	0.83	0.75	6.7	2.4	2.7	IE2
460	Δ	60	37.00	-/-	58.00	1782	198.0	94.5	94.7	94.2	0.85	0.81	0.71	7.5	2.8	3.0	IE3
IM V6 / IM 1031		FS 225 S		IP55				IEC/EN 60034		IEC, DIN, ISO, VDE, EN							
Environmental conditions : -20 °C - +40 °C / 1,000 m									Locked rotor time (hot / cold) : 36.8 s 55.7 s								

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	65 / 78 dB(A) ^{2) 3)}	68 / 82 dB(A) ^{2) 3)}	External earthing terminal	With (standard)
Moment of inertia	0.4200 kg m ²		Vibration severity grade	A
Bearing DE NDE	6213 C3	6213 C3	Thermal class	F
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad} ¹⁾ for coupling operation 50 60Hz	20000 h	16000 h	Direction of rotation	bidirectional
Relubrication interval/quantity DE NDE	20 g 20 g	8000 h	Frame material	cast iron
Lubricants	Unirex N3		Net weight of the motor (IM B3)	285 kg
Regreasing device	With		Coating (paint finish)	Special paint finish C3
Grease nipple	M10x1 DIN 3404 A		Color, paint shade	RAL7030
Type of bearing	Locating bearing NDE		Motor protection	(A) without (Standard)
Condensate drainage holes	With (standard)		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	35 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	27 mm - 35 mm
Type of terminal box	TB1 L01	Cable entry	2xM50x1,5
Contact screw thread	M8		

Notes:

I_A/I_N = locked rotor current / current nominal 1) L_{10mh} according to DIN ISO 281 10/2010 3) Value is valid only for DOL operation with motor design IC411

M_K/M_N = locked rotor torque / torque nominal 2) at rated power / at full load

M_B/M_N = break down torque / nominal torque

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents		
IN LVM		SPC						
SIEMENS	document type	datasheet			document status			
					released			
	title	1MB1533-2BB03-4DA4-Z			document number			
© INNOMOTICS 2023	B02+C02+L23				rev.	creation date	language	Page
					951	2023-12-14	en	1/2

SIMOTICS XP - 225 S - IM V6 - 4p

Notes:

responsible dep. IN LVM	technical reference	created by SPC	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
	document type datasheet			document status released			
	title 1MB1533-2BB03-4DA4-Z			document number			
© INNOMOTICS 2023	B02+C02+L23			rev. 951	creation date 2023-12-14	language en	Page 2/2