

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3282B

SIMOTICS XP - 280 M - IM B3 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data II 3G Ex ec IIC T3 Gc
-/-

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
DOL duty (S1) - 155(F) to 130(B)																	
400	Δ	50	90.00	-/-	157.00	1485	580.0	95.2	95.5	95.3	0.87	0.84	0.76	7.2	2.6	3.0	IE3
690	Y	50	90.00	-/-	91.00	1485	580.0	95.2	95.5	95.3	0.87	0.84	0.76	7.2	2.6	3.0	IE3
460	Δ	60	104.00	-/-	158.00	1785	560.0	95.0	95.3	94.9	0.87	0.85	0.77	7.0	2.6	2.9	IE2
460	Δ	60	90.00	-/-	136.00	1788	480.0	95.4	95.5	94.9	0.87	0.84	0.75	8.0	2.9	3.3	IE3
IM B3 / IM 1001		FS 280 M				IP55			IEC/EN 60034		IEC, DIN, ISO, VDE, EN						
Environmental conditions : -20 °C - +40 °C / 1,000 m									Locked rotor time (hot / cold) : 31.7 s 46.3 s								

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	70 / 84 dB(A) ^{2) 3)}	79 / 93 dB(A) ^{2) 3)}	External earthing terminal	With (standard)
Moment of inertia	1.7000 kg m ²		Vibration severity grade	A
Bearing DE NDE	6317 C3	6317 C3	Thermal class	F
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad} ¹⁾ for coupling operation 50 60Hz	40000 h	32000 h	Direction of rotation	bidirectional
Relubrication interval/quantity DE NDE	30 g 30 g	8000 h	Frame material	cast iron
Lubricants	Unirex N3		Net weight of the motor (IM B3)	670 kg
Regreasing device	With (standard)		Coating (paint finish)	Standard paint finish C2
Grease nipple	M10x1 DIN 3404 A		Color, paint shade	RAL7030
Type of bearing	Locating bearing NDE		Motor protection	(A) without (Standard)
Condensate drainage holes	With (standard)		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	120 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	34 mm - 45 mm
Type of terminal box	TB1 N01	Cable entry	2xM63x1,5
Contact screw thread	M10		

Notes:
I_A/I_N = locked rotor current / current nominal
M_K/M_N = locked rotor torque / torque nominal
M_B/M_N = break down torque / nominal torque
1) L_{10mh} according to DIN ISO 281 10/2010
2) at rated power / at full load
3) Value is valid only for DOL operation with motor design IC411

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.	Link documents
IN LVM		SPC			
SIEMENS	document type				document status
	datasheet				released
	title				document number
	1MB1533-2DB23-4AA4				
© INNOMOTICS 2023		rev.	creation date	language	Page
		951	2023-12-14	en	1/1