

SIMOTICS XP - 132 M - IM V15 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

-/-

Electrical data

U [V]	Δ / Y	f [Hz]	P [kW]	P [hp]	I [A]	n [1/min]	M [Nm]	$\eta^{3)}$			$\cos\varphi^{3)}$			I_A/I_N	M_A/M_N	M_K/M_N	IE-CL
								4/4	3/4	2/4	4/4	3/4	2/4	I_I/I_N	T_I/T_N	T_B/T_N	
DOL duty (S1) - 155(F) to 130(B)																	
400	Δ	50	6.15	-/-	12.00	1470	40.0	90.9	90.9	90.4	0.81	0.75	0.65	10.0	3.2	4.5	IE3
690	Y	50	6.15	-/-	7.00	1470	40.0	90.9	90.9	90.4	0.81	0.75	0.65	10.0	3.2	4.5	IE3
460	Δ	60	6.15	-/-	10.30	1775	33.1	91.8	91.4	89.8	0.82	0.77	0.67	11.7	3.3	5.1	IE3
IM V15 / IM 2011			FS 132 M			IP56		IEC/EN 60034									

Locked rotor time (hot / cold) : 19.4 s | 25.4 s

The efficiency values and efficiency class according to EuP directive are valid for standard power ratings under standard conditions.

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	68 / 76 dB(A) ^{2) 3)}	68 / 80 dB(A) ^{2) 3)}	Thermal class	F
Moment of inertia	0.0404 kg m ²		Duty type	S1
Bearing DE NDE	6308 2Z C3	6308 2Z C3	Direction of rotation	bidirectional
bearing lifetime			Frame material	cast iron
L _{10mh} F _{Rad min} for coupling operation 50 60Hz ¹⁾	20000 h	16000 h	Net weight of the motor	123 kg
Regreasing device	Without		Motor weight incl. options	124 kg
Grease nipple	-/-		Coating (paint finish)	Standard paint finish C2
Type of bearing	Locating bearing DE		Color, paint shade	RAL7030
Condensate drainage holes	Without		Motor protection	(A) without (Standard)
External earthing terminal	With (standard)		Method of cooling	IC411 - self ventilated, surface cooled
Vibration severity grade	A			

Terminal box

Terminal box position	top	Max. cross-sectional area	6 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	11 mm - 21 mm
Type of terminal box	TB1 H21	Cable entry	-/-
Contact screw thread	M4		

Notes:

I_A/I_N = locked rotor current / current nominal
 M_A/M_N = locked rotor torque / torque nominal
 M_K/M_N = break down torque / nominal torque

1) L_{10mh} according to DIN ISO 281 10/2010
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
IN LVM		SPC					
	document type			document status			
	datasheet			released			
	title			document number			
	1MB1553-1CB23-4WA4-Z						
	H00+H22+N08			rev.	creation date	language	Page
© INNOMOTICS 2023				951	2023-12-14	en	1/2

SIMOTICS XP - 132 M - IM V15 - 4p

H00	Canopy	N08	Temperature class 155 (F), utilised to 130 (B), cooling medium temperature 60°C, power reduced
H22	IP 56 degree of protection		

Notes:

responsible dep. IN LVM	technical reference	created by SPC	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
	document type datasheet			document status released			
	title 1MB1553-1CB23-4WA4-Z			document number			
© INNOMOTICS 2023	H00+H22+N08			rev. 951	creation date 2023-12-14	language en	Page 2/2