

SIMOTICS XP - 180 M - IM B35 - 2p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

-/-

Electrical data

U	Δ / Y	f	P	P	I	n	M	$\eta^{3)}$			$\cos \varphi^{3)}$			I_A/I_N	M_A/M_N	M_K/M_N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I_I/I_N	T_I/T_N	T_B/T_N	

DOL duty (S1) - 155(F) to 130(B)

[illegible]

Converter duty (S9) - 155(F) to 130(B)

40	Δ	5	1.22		25	270	43.2		0.88	Type of converter	Voltage source converter, general.
200	Δ	25	9.4		34	1,455	61.8		0.88		
400	Δ	50	20.5		36	2,955	66		0.89		
400	Δ	76	20.5		35	4490	43.6		0.90		

IM B35 / IM 2001

FS 180 M

IP55

--	--

--

Environmental conditions : -20 °C - +40 °C / 1,000 m

Locked rotor time (hot / cold) : 23.5 s | 35.7 s

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	72 / 80 dB(A) ^{2) 3)}	77 / 89 dB(A) ^{2) 3)}	Thermal class	F
Moment of inertia	0.0889 kg m²		Duty type	S1
Bearing DE NDE	6310 C3	6310 C3	Direction of rotation	bidirectional
bearing lifetime			Frame material	cast iron
L _{10mh} F _{Rad, min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Net weight of the motor	248 kg
Regreasing device	Without		Motor weight incl. options	248 kg
Grease nipple	-/-		Coating (paint finish)	Special paint finish C3
Type of bearing	Locating bearing DE		Color, paint shade	RAL7030
Condensate drainage holes	Without		Motor protection	(B) 3 PTC thermistors - for tripping (2 terminals)
External earthing terminal	With (standard)		Method of cooling	IC411 - self ventilated, surface cooled
Vibration severity grade	A			

Terminal box

Terminal box position	top	Max. cross-sectional area	16 mm²
Material of terminal box	cast iron	Cable diameter from ... to ...	19 mm - 28 mm
Type of terminal box	TB1 J21	Cable entry	-/-
Contact screw thread	M5		

Notes:

I_A/I_N = locked rotor current / current nominal
 M_A/M_N = locked rotor torque / torque nominal
 M_K/M_N = break down torque / nominal torque

1) L_{10mh} according to DIN ISO 281 10/2010
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
IN LVM		SPC					
	document type			document status			
	datasheet			released			
	title			document number			
	1MB1553-1EA29-0JB4-Z						
	B43+C02+M4B			rev.	creation date	language	Page
© INNOMOTICS 2023				951	2023-12-14	en	1/2

SIMOTICS XP - 180 M - IM B35 - 2p

Notes:

responsible dep. IN LVM	technical reference	created by SPC	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents		
	document type datasheet				document status released			
	title 1MB1553-1EA29-0JB4-Z				document number			
© INNOMOTICS 2023	B43+C02+M4B				rev. 951	creation date 2023-12-14	language en	Page 2/2