

SIMOTICS XP - 200 L - IM B3 - 2p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

-/-

Electrical data

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
DOL duty (S1) - 155(F) to 130(B)																	
380	Δ	50	30.00	-/-	56.00	2955	97.0	93.3	93.6	93.3	0.87	0.83	0.75	7.0	2.5	3.3	IE3
660	Y	50	30.00	-/-	32.50	2955	97.0	93.3	93.6	93.3	0.87	0.83	0.75	7.0	2.5	3.3	IE3
440	Δ	60	30.00	-/-	49.00	3560	80.0	92.4	92.2	91.4	0.87	0.83	0.74	7.6	2.9	3.6	IE3
IM B3 / IM 1001			FS 200 L			IP65		IEC/EN 60034								Grade 3	

Environmental conditions : -20 °C - +40 °C / 1.000 m

Locked rotor time (hot / cold) : 34.3 s | 52.7 s

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	76 / 84 dB(A) ^{2) 3)}	77 / 84 dB(A) ^{2) 3)}	Thermal class	F
Moment of inertia	0.1500 kg m²		Duty type	S1
Bearing DE NDE	6312 C3	6312 C3	Direction of rotation	bidirectional
bearing lifetime			Frame material	cast iron
L _{10mh} F _{rad min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Net weight of the motor	315 kg
Regreasing device	Without		Motor weight incl. options	315 kg
Grease nipple	-/		Coating (paint finish)	Special paint finish C3
Type of bearing	Locating bearing DE		Color, paint shade	RAL7030
Condensate drainage holes	Without		Motor protection	(B) 3 PTC thermistors - for tripping (2 terminals)
External earthing terminal	With (standard)		Method of cooling	IC411 - self ventilated, surface cooled
Vibration severity grade	A			

Terminal box

Terminal box position	top	Max. cross-sectional area	35 mm²
Material of terminal box	cast iron	Cable diameter from ... to ...	27 mm - 35 mm
Type of terminal box	TB1 L21	Cable entry	-/-
Contact screw thread	M6		

Notes:

I_A/I_N = locked rotor current / current nominal
 M_A/M_N = locked rotor torque / torque nominal
 M_K/M_N = break down torque / nominal torque

1) L_{10mh} according to DIN ISO 281 10/2010
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
IN LVM		SPC					
	document type			document status			
	datasheet			released			
	title			document number			
	1MB1553-2AA43-3AB4-Z						
	C02+D32+D34+H20			rev.	creation date	language	Page
© INNOMOTICS 2023				951	2023-12-14	en	1/2

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CD3204A

SIMOTICS XP - 200 L - IM B3 - 2p

Special design

C02	VIK version	D34	China Energy Efficiency Label
D32	Ex certification for China	H20	IP 65 degree of protection

Notes:

responsible dep. IN LVM	technical reference	created by SPC	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents 	
	document type datasheet			document status released			
	title 1MB1553-2AA43-3AB4-Z			document number			
© INNOMOTICS 2023	C02+D32+D34+H20			rev. 951	creation date 2023-12-14	language en	Page 2/2