



Figure similar

Data sheet for SIMOTICS M-1PH8

Article No. : 1PH8083-1DG12-0BG1

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data

		P _N [kW]	M _N [Nm]	I _N [A]	U _N [V]	f _N [Hz]	n _N [rpm]	M _{max} [Nm]	I _{max} [A]	n _{max} [rpm]	M ₀ [Nm]	I ₀ [A]	η	cos φ	I _μ [A]
Y	ALM 400V	4.1	17.0	11.3	332	80.0	2,300	45	24.0	10,000	21.0	12	0.852	0.78	5.7
	BLM/SLM 400V	3.7	18.0	11.6	293	70.2	2,000	45	24.0	10,000	21.0	12	0.832	0.79	5.7
	ALM/BLM/SLM 480V	4.6	17.0	11.2	376	91.6	2,650	45	24.0	10,000	21.0	12	0.862	0.78	5.7

Mechanical data	
Motor type	Squirrel cage asynchronous motor
Shaft height	80
Cooling	Forced ventilation NDE -> DE
Vibration severity grade	R/A
Shaft and flange accuracy	R
Degree of protection	IP55
Design acc. to Code I	IM B5 (IM V1, IM V3)
Temperature monitoring	Pt1000 temperature sensor in the stator winding
Color	Standard (Anthracite RAL 7016)
Type of the bearing	Standard with fixed bearing
Shaft extension	Plain shaft
Encoder system	Incremental encoder 22 bit with commutation position 11 bit, max. encoder speed = 12000 rpm

Physical constants	
Thermal time constant	10 min
Moment of inertia	64 kgcm ²
Weight (approx.)	32 kg

Connection	
Type of electrical connection	Power connector
Position of the connection	Power connector, top
Power connection	NDE
Signal connection	left

Cooling data and sound pressure level	
Airflow, min.	0.02 m ³ /s
Sound pressure level LpA(1m) motor + external fan operation 50 HZ rated load, tolerance + 3dB	70 dB ¹⁾
Air discharge	axial
Pressure drop	95 Pa

¹⁾ at a rated frequency of 4 kHz and a speed range of up to 5000 rpm