



Figure similar

Data sheet for SIMOTICS M-1PH8

Article No. : 1PH8087-1DG10-1GE1

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data

		P _N [kW]	M _N [Nm]	I _N [A]	U _N [V]	f _N [Hz]	n _N [rpm]	M _{max} [Nm]	I _{max} [A]	n _{max} [rpm]	M ₀ [Nm]	I ₀ [A]	η	cos φ	I _μ [A]
Y	ALM 400V	5.4	22.0	13.7	353	79.8	2,300	63	31.0	10,000	27.0	15	0.859	0.79	6.8
	BLM/SLM 400V	4.9	23.0	14.1	320	69.8	2,000	63	31.0	10,000	27.0	15	0.853	0.78	7.3
	ALM/BLM/SLM 480V	6.0	22.0	13.6	390	91.6	2,650	63	31.0	10,000	27.0	15	0.884	0.79	6.5

Mechanical data	
Motor type	Squirrel cage asynchronous motor
Shaft height	80
Cooling	Forced ventilation NDE -> DE
Vibration severity grade	R/A
Shaft and flange accuracy	R
Degree of protection	IP55
Design acc. to Code I	IM B3 (IM V5, IM V6)
Temperature monitoring	Pt1000 temperature sensor in the stator winding
Color	Standard (Anthracite RAL 7016)
Type of the bearing	Standard
Shaft extension	Feather key with full key balancing
Encoder system	Incremental encoder 22 bit with commutation position 11 bit, max. encoder speed = 12000 rpm

Physical constants	
Thermal time constant	10 min
Moment of inertia	89 kgcm ²
Weight (approx.)	39 kg

Connection	
Type of electrical connection	Power connector
Position of the connection	Power connector, top
Power connection	right
Signal connection	DE

Cooling data and sound pressure level	
Airflow, min.	0.02 m ³ /s
Sound pressure level LpA(1m) motor + external fan operation 50 HZ rated load, tolerance + 3dB	70 dB ¹⁾
Air discharge	axial
Pressure drop	95 Pa

¹⁾ at a rated frequency of 4 kHz and a speed range of up to 5000 rpm