

Data sheet for SIMOTICS M-1PH8

Article No. : 1PH8101-3HF02-2AA2-Z
K24+U65



Figure similar

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data

		P _N [kW]	M _N [Nm]	I _N [A]	U _N [V]	f _N [Hz]	n _N [rpm]	M _{max} [Nm]	I _{max} [A]	n _{max} [rpm]	M ₀ [Nm]	I ₀ [A]	η	cos φ	I _μ [A]
Y	ALM 400V	4.3	23.0	12.5	304	60.8	1,750	60	32.0	5,000	29.0	14	0.852	0.800	6.0
	BLM/SLM 400V	3.7	24.0	12.5	265	52.4	1,500	60	32.0	5,000	29.0	14	0.835	0.800	6.0
	ALM/BLM/SLM 480V	4.7	22.0	12.5	343	69.0	2,000	60	32.0	5,000	29.0	14	0.871	0.790	6.0

Mechanical data

Motor type	Squirrel cage asynchronous motor
Shaft height	100
Cooling	Forced ventilation DE -> NDE
Vibration severity grade	A
Shaft and flange accuracy	N
Degree of protection	IP55
Design acc. to Code I	IM B5 (IM V1, IM V3)
Temperature monitoring	Pt1000 temperature sensor in the stator winding
Color	Primer (pale green)
Type of the bearing	Standard
Shaft end	Feather key with half key balancing
Encoder system	Incremental encoder HTL 1024 S/R, max. encoder speed = 9000 rpm

Physical constants

Thermal time constant	20 min
Moment of inertia with brake	186 kgcm ²
Weight with brake (approx.)	63 kg

Connection

Type of electrical connection	Terminal box
Position of the connection	NDE top
Power connection	right
Signal connection	DE
Terminal box designation	gk813

Cooling data and sound pressure level

Airflow, min.	0.04 m ³ /s
Sound pressure level L _{pA} (1m) motor + external fan operation 50 HZ rated load, tolerance + 3dB	70 dB ¹⁾
Air discharge	axial
Pressure drop	110 Pa

Holding brake

Holding torque	60 ... 150 Nm ²⁾
Moment of inertia	48 kgcm ²
Power supply voltage	DC 24 V ± 10%
Coil current	4.7 A
Permissible brake work	7 kJ
Speed (Emergency Stop)	4,500 rpm
Number of emergency stops	2,000
Number of emergency stops per hour	3
Opening time	500 ms
Closing time	60 ms

External fan

Max. power consumption

3 AC 400 V / 50 Hz (±10%)	0.10 A
3 AC 400 V / 60 Hz (±10%)	0.08 A
3 AC 480 V / 60 Hz (±10%)	0.11 A

Special design

K24	Primer
U65	24 V DC holding brake

¹⁾ at a rated frequency of 4 kHz and a speed range of up to 5000 rpm

²⁾ Holding torque [Nm]: On motors with shaft height 100 ... 160, the holding torque can be gradually set using an adjusting ring within the value range specified (factory setting 100 % of the possible holding torque). The dynamic braking torque is approx. 70 % of the set holding torque.