



Figure similar

Data sheet for SIMOTICS M-1PH8

Article No. : 1PH8103-1HF13-1HB2-Z
K09+X01

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data

		P _N [kW]	M _N [Nm]	I _N [A]	U _N [V]	f _N [Hz]	n _N [rpm]	M _{max} [Nm]	I _{max} [A]	n _{max} [rpm]	M ₀ [Nm]	I ₀ [A]	η	cos φ	I _μ [A]
Y	ALM 400V	6.3	34.0	13.1	412	60.8	1,750	60	23.0	9,000	38.0	14	0.859	0.810	6.0
	BLM/SLM 400V	5.5	35.0	13.5	368	52.4	1,500	60	23.0	9,000	38.0	14	0.852	0.800	6.5
	ALM 480V	7.7	33.0	12.7	480	76.1	2,200	60	23.0	9,000	38.0	14	0.880	0.830	5.8
	BLM/SLM 480V	7.0	33.0	12.7	460	69.1	2,000	60	23.0	9,000	38.0	14	0.894	0.810	5.8

Mechanical data

Motor type	Squirrel cage asynchronous motor
Shaft height	100
Cooling	Forced ventilation NDE -> DE
Vibration severity grade	S/A
Shaft and flange accuracy	R
Degree of protection	IP55
Design acc. to Code I	IM B35 (IM V15, IM V35)
Temperature monitoring	Pt1000 temperature sensor in the stator winding
Color	Jet black, matt RAL 9005
Type of the bearing	Standard
Shaft end	Feather key with full key balancing
Encoder system	Incremental encoder HTL 1024 S/R, max. encoder speed = 9000 rpm

Physical constants

Thermal time constant	20 min
Moment of inertia	172 kgcm ²
Weight (approx.)	51 kg

Connection

Type of electrical connection	Terminal box
Position of the connection	NDE right
Power connection	top
Signal connection	DE
Terminal box designation	gk823

Cooling data and sound pressure level

Airflow, min.	0.04 m³/s
Sound pressure level LpA(1m) motor + external fan operation 50 HZ rated load, tolerance + 3dB	70 dB ¹⁾
Air discharge	axial
Pressure drop	110 Pa

External fan

Max. power consumption

3 AC 400 V / 50 Hz (±10%)	0.08 A
3 AC 400 V / 60 Hz (±10%)	0.07 A
3 AC 480 V / 60 Hz (±10%)	0.11 A

Special design

- K09 Terminal box NDE right
- X01 Paint finish: Jet black, matt RAL 9005

¹⁾at a rated frequency of 4 kHz and a speed range of up to 5000 rpm