



Figure similar

Data sheet for SIMOTICS M-1PH8

Article No. : 1PH8103-1HF23-1BA2

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data

		P _N [kW]	M _N [Nm]	I _N [A]	U _N [V]	f _N [Hz]	n _N [rpm]	M _{max} [Nm]	I _{max} [A]	n _{max} [rpm]	M ₀ [Nm]	I ₀ [A]	η	cos φ	I _μ [A]
Y	ALM 400V	8.2	45.0	19.7	364	61.4	1,750	85	37.0	9,000	48.0	20	0.851	0.820	8.6
	BLM/SLM 400V	7.1	45.0	19.7	317	53.0	1,500	85	37.0	9,000	48.0	20	0.827	0.820	8.6
	ALM/BLM/SLM 480V	9.4	45.0	19.7	411	69.7	2,000	85	37.0	9,000	48.0	20	0.869	0.820	8.5

Mechanical data

Motor type	Squirrel cage asynchronous motor
Shaft height	100
Cooling	Water cooling
Vibration severity grade	R/A
Shaft and flange accuracy	R
Degree of protection	IP65
Design acc. to Code I	IM B35 (IM V15, IM V35)
Temperature monitoring	Pt1000 temperature sensor in the stator winding
Color	Standard (Anthracite RAL 7016)
Type of the bearing	Standard with fixed bearing
Shaft end	Feather key with full key balancing
Encoder system	Incremental encoder HTL 1024 S/R, max. encoder speed = 9000 rpm

Physical constants

Thermal time constant	10 min
Moment of inertia	172 kgcm ²
Weight (approx.)	60 kg

Connection

Type of electrical connection	Terminal box
Position of the connection	NDE top
Power connection	right
Signal connection	DE
Terminal box designation	gk823

Cooling data and sound pressure level

Flow rate, min.	8 l/min
Sound pressure level L _{pA} (1m) motor rated load, tolerance + 3dB	68 dB ¹⁾
Pressure drop	0.4 bar
NDE thread connection	0.25 Inches

Cooling water specification

pH value	6 ... 9
Total hardness	1.7 mmol/l
Electrical conductivity	500 μS/cm
Chloride ions	40 mg/l
Sulfate ions	50 mg/l
Nitrate ions	50 mg/l
Dissolved substances	340 mg/l
Maximum particle size	100 μm
Antifreeze/corrosion protection	20 ... 30 %

¹⁾ at a rated frequency of 4 kHz and a speed range of up to 5000 rpm