



Figure similar

Data sheet for SIMOTICS M-1PH8

Article No. : 1PH8133-1DG00-0HB1-Z
K10

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data

		P _N [kW]	M _N [Nm]	I _N [A]	U _N [V]	f _N [Hz]	n _N [rpm]	M _{max} [Nm]	I _{max} [A]	n _{max} [rpm]	M ₀ [Nm]	I ₀ [A]	η	cos φ	l _μ [A]
Y	ALM 400V	22.5	93.0	44.0	400	78.1	2,300	250	117.0	8,000	126.0	54	0.933	0.840	18.1
	BLM/SLM 400V	20.0	96.0	45.0	350	68.1	2,000	250	117.0	8,000	126.0	54	0.919	0.850	18.1
	ALM/BLM/SLM 480V	24.0	86.0	41.0	456	89.6	2,650	250	117.0	8,000	126.0	54	0.949	0.830	18.1

Mechanical data

Motor type	Squirrel cage asynchronous motor
Shaft height	132
Cooling	Forced ventilation DE -> NDE
Vibration severity grade	S/A
Shaft and flange accuracy	R
Degree of protection	IP55
Design acc. to Code I	IM B3 (IM V5, IM V6, IM B6, IM B7, IM B8)
Temperature monitoring	Pt1000 temperature sensor in the stator winding
Color	Standard (Anthracite RAL 7016)
Type of the bearing	Standard
Shaft extension	Plain shaft
Encoder system	Incremental encoder 22 bit with commutation position 11 bit, max. encoder speed = 12000 rpm

Physical constants

Thermal time constant	30 min
Moment of inertia	760 kgcm²
Weight (approx.)	106 kg

Connection

Type of electrical connection	Terminal box
Position of the connection	NDE left
Power connection	below
Signal connection	DE
Terminal box designation	gk843

Cooling data and sound pressure level

Airflow, min.	0.09 m³/s
Sound pressure level LpA(1m) motor + external fan operation 50 HZ rated load, tolerance + 3dB	70 dB ¹⁾
Air discharge	axial
Pressure drop	140 Pa

Special design

K10 Terminal box NDE left

¹⁾ at a rated frequency of 4 kHz and a speed range of up to 5000 rpm