

SIMOTICS M compact asynchronous motor 1000 r/min 12 kW 115 Nm 30 A 319 V 1150 r/min 13.5 kW 112 Nm 29 A 361 V 1350 r/min 15 kW 106 Nm 28 A 417 V 1500 r/min 16.6 kW 106 Nm 28 A 459 V forced ventilation; direction of air flow DE--> NDE; IP55 degree of protection INCREMENT. ENCODER HTL 1024 S/R (ENCODER HTL 1024 S/R) CONNECTION VIA TERMINAL BLOCK (ADDITIONAL TERMINAL BOX) Design IM B35 (IM V15, (IM V35) SHAFT WITH FITTED KEY HALF-KEY BALANCING BEARING: STANDARD VIBRATION SEVERITY GRADE A; SHAFT A.FLANGE ACCURACY GR.N TERMINAL BOX (ABOVE) CABLE ENTRY ON THE RIGHT SIGNAL CONNECTION D-END U65: holding brake 24 V DC V90: shaft extension 42x 110 mm 1PH7-compatible

Further information

Industry Online Support (Manuals, Catalogs, Certificates, FAQ, ...)
<https://support.industry.siemens.com/cs/products?mfn=ps&lc=en-WW>
Industry Mall (Online ordering system)
<https://mall.industry.siemens.com>

