



Figure similar

Data sheet for SIMOTICS M-1PH8

Article No. : 1PH8137-1DD00-2BB1

Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :

Engineering data

|   |              | P <sub>N</sub><br>[kW] | M <sub>N</sub><br>[Nm] | I <sub>N</sub><br>[A] | U <sub>N</sub><br>[V] | f <sub>N</sub><br>[Hz] | n <sub>N</sub><br>[rpm] | M <sub>max</sub><br>[Nm] | I <sub>max</sub><br>[A] | n <sub>max</sub><br>[rpm] | M <sub>0</sub><br>[Nm] | I <sub>0</sub><br>[A] | η     | cos φ | I <sub>μ</sub><br>[A] |
|---|--------------|------------------------|------------------------|-----------------------|-----------------------|------------------------|-------------------------|--------------------------|-------------------------|---------------------------|------------------------|-----------------------|-------|-------|-----------------------|
| Y | ALM 400V     | 19.5                   | 162.0                  | 43.0                  | 350                   | 39.9                   | 1,150                   | 405                      | 108.0                   | 8,000                     | 176.0                  | 45                    | 0.891 | 0.880 | 16.1                  |
|   | BLM/SLM 400V | 17.0                   | 162.0                  | 43.0                  | 307                   | 34.8                   | 1,000                   | 405                      | 108.0                   | 8,000                     | 176.0                  | 45                    | 0.881 | 0.880 | 15.1                  |
|   | ALM 480V     | 24.0                   | 153.0                  | 41.0                  | 447                   | 51.5                   | 1,500                   | 405                      | 108.0                   | 8,000                     | 176.0                  | 45                    | 0.890 | 0.860 | 15.9                  |
|   | BLM/SLM 480V | 22.0                   | 156.0                  | 42.0                  | 404                   | 46.4                   | 1,350                   | 405                      | 108.0                   | 8,000                     | 176.0                  | 45                    | 0.902 | 0.860 | 15.9                  |

Mechanical data

|                           |                                                                                             |
|---------------------------|---------------------------------------------------------------------------------------------|
| Motor type                | Squirrel cage asynchronous motor                                                            |
| Shaft height              | 132                                                                                         |
| Cooling                   | Forced ventilation DE -> NDE                                                                |
| Vibration severity grade  | R/A                                                                                         |
| Shaft and flange accuracy | R                                                                                           |
| Degree of protection      | IP55                                                                                        |
| Design acc. to Code I     | IM B3 (IM V5, IM V6, IM B6, IM B7, IM B8)                                                   |
| Temperature monitoring    | Pt1000 temperature sensor in the stator winding                                             |
| Color                     | Standard (Anthracite RAL 7016)                                                              |
| Type of the bearing       | Standard with fixed bearing                                                                 |
| Shaft end                 | Feather key with half key balancing                                                         |
| Encoder system            | Incremental encoder 22 bit with commutation position 11 bit, max. encoder speed = 12000 rpm |

External fan

Max. power consumption

|                           |        |
|---------------------------|--------|
| 3 AC 400 V / 50 Hz (±10%) | 0.10 A |
| 3 AC 400 V / 60 Hz (±10%) | 0.12 A |
| 3 AC 480 V / 60 Hz (±10%) | 0.12 A |

<sup>1)</sup> at a rated frequency of 4 kHz and a speed range of up to 5000 rpm

Physical constants

|                       |                         |
|-----------------------|-------------------------|
| Thermal time constant | 30 min                  |
| Moment of inertia     | 1,090 kgcm <sup>2</sup> |
| Weight (approx.)      | 141 kg                  |

Connection

|                               |              |
|-------------------------------|--------------|
| Type of electrical connection | Terminal box |
| Position of the connection    | NDE top      |
| Power connection              | left         |
| Signal connection             | DE           |
| Terminal box designation      | gk833        |

Cooling data and sound pressure level

|                                                                                               |                     |
|-----------------------------------------------------------------------------------------------|---------------------|
| Airflow, min.                                                                                 | 0.09 m³/s           |
| Sound pressure level LpA(1m) motor + external fan operation 50 HZ rated load, tolerance + 3dB | 70 dB <sup>1)</sup> |
| Air discharge                                                                                 | axial               |
| Pressure drop                                                                                 | 140 Pa              |