



Figure similar

Data sheet for SIMOTICS M-1PH8

Article No. : 1PH8137-1JG13-2GA2-Z
V90

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data

		P _N [kW]	M _N [Nm]	I _N [A]	U _N [V]	f _N [Hz]	n _N [rpm]	M _{max} [Nm]	I _{max} [A]	n _{max} [rpm]	M ₀ [Nm]	I ₀ [A]	η	cos φ	I _μ [A]
Y	ALM 400V	29.0	120.0	56.0	398	77.9	2,300	340	152.0	4,600	176.0	73	0.929	0.860	21.9
	BLM/SLM 400V	28.0	134.0	60.0	350	68.1	2,000	340	152.0	4,600	176.0	73	0.924	0.870	21.5
	ALM 480V	31.0	106.0	52.0	494	94.4	2,800	340	152.0	4,600	176.0	73	0.920	0.820	22.4
	BLM/SLM 480V	30.0	108.0	52.0	460	89.4	2,650	340	152.0	4,600	176.0	73	0.941	0.830	22.4

Mechanical data

Motor type	Squirrel cage asynchronous motor
Shaft height	132
Cooling	Forced ventilation NDE -> DE
Vibration severity grade	R/A
Shaft and flange accuracy	R
Degree of protection	IP55
Design acc. to Code I	IM B35 (IM V15, IM V35)
Temperature monitoring	Pt1000 temperature sensor in the stator winding
Color	Standard (Anthracite RAL 7016)
Type of the bearing	Standard
Shaft end	Feather key with half key balancing
Encoder system	Incremental encoder HTL 2048 S/R, max. encoder speed = 4600 rpm

Physical constants

Thermal time constant	30 min
Moment of inertia	1,090 kgcm²
Weight (approx.)	141 kg

Connection

Type of electrical connection	Terminal box
Position of the connection	NDE top
Power connection	right
Signal connection	DE
Terminal box designation	gk833

Cooling data and sound pressure level

Airflow, min.	0.09 m³/s
Sound pressure level LpA(1m) motor + external fan operation 50 HZ rated load, tolerance + 3dB	70 dB ¹⁾
Air discharge	axial
Pressure drop	140 Pa

External fan

Max. power consumption

3 AC 400 V / 50 Hz (±10%)	0.11 A
3 AC 400 V / 60 Hz (±10%)	0.13 A
3 AC 480 V / 60 Hz (±10%)	0.13 A

Special design

V90 1PH7-compatible shaft end 42 mm x 110 mm

¹⁾ at a rated frequency of 4 kHz and a speed range of up to 5000 rpm