

Data sheet for SIMOTICS M-1PH8

Article No. : 1PH8163-1DB03-0HC1



Figure similar

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data

		P _N [kW]	M _N [Nm]	I _N [A]	U _N [V]	f _N [Hz]	n _N [rpm]	M _{max} [Nm]	I _{max} [A]	n _{max} [rpm]	M ₀ [Nm]	I ₀ [A]	η	cos φ	I _μ [A]
Y	ALM 400V	12.0	229.0	30.0	325	17.6	500	570	70.0	6,500	239.0	30	0.819	0.90	8.9
	BLM/SLM 400V	9.5	227.0	30.0	260	14.3	400	570	70.0	6,500	239.0	30	0.828	0.91	8.1
	ALM/BLM/SLM 480V	14.5	231.0	30.0	370	21.0	600	570	70.0	6,500	239.0	30	0.851	0.90	8.1

Mechanical data	
Motor type	Squirrel cage asynchronous motor
Shaft height	160
Cooling	Forced ventilation DE -> NDE
Vibration severity grade	S/A
Shaft and flange accuracy	R
Degree of protection	IP55
Design acc. to Code I	IM B35 (IM V15, IM V35)
Temperature monitoring	Pt1000 temperature sensor in the stator winding
Color	Standard (Anthracite RAL 7016)
Type of the bearing	Standard
Shaft extension	Plain shaft
Encoder system	Incremental encoder 22 bit with commutation position 11 bit, max. encoder speed = 12000 rpm

Physical constants	
Thermal time constant	35 min
Moment of inertia	2,160 kgcm ²
Weight (approx.)	196 kg

Connection	
Type of electrical connection	Terminal box
Position of the connection	NDE top
Power connection	NDE
Signal connection	left
Terminal box designation	gk863

Cooling data and sound pressure level	
Airflow, min.	0.16 m ³ /s
Sound pressure level LpA(1m) motor + external fan operation 50 HZ rated load, tolerance + 3dB	73 dB ¹⁾
Air discharge	axial
Pressure drop	200 Pa

¹⁾ at a rated frequency of 4 kHz and a speed range of up to 5000 rpm