

Data sheet for SIMOTICS M-1PH8

Article No. : 1PH8165-1HG10-1GA1



Figure similar

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data

		P _N [kW]	M _N [Nm]	I _N [A]	U _N [V]	f _N [Hz]	n _N [rpm]	M _{max} [Nm]	I _{max} [A]	n _{max} [rpm]	M ₀ [Nm]	I ₀ [A]	η	cos φ	I _μ [A]
Y	ALM 400V	44.0	183.0	85.0	394	77.4	2,300	620	278.0	6,500	302.0	122	0.932	0.860	31.0
	BLM/SLM 400V	41.0	196.0	88.0	350	67.4	2,000	620	278.0	6,500	302.0	122	0.927	0.870	32.4
	ALM/BLM/SLM 480V	50.0	180.0	85.0	440	89.0	2,650	620	278.0	6,500	302.0	122	0.932	0.870	28.9

Mechanical data

Motor type	Squirrel cage asynchronous motor
Shaft height	160
Cooling	Forced ventilation NDE -> DE
Vibration severity grade	R/A
Shaft and flange accuracy	R
Degree of protection	IP55
Design acc. to Code I	IM B3 (IM V5, IM V6, IM B6, IM B7, IM B8)
Temperature monitoring	KTY84 temperature sensor in the stator winding
Color	Standard (Anthracite RAL 7016)
Type of the bearing	Standard
Shaft end	Feather key with full key balancing
Encoder system	Incremental encoder HTL 1024 S/R, max. encoder speed = 9000 rpm

External fan

Max. power consumption

3 AC 400 V / 50 Hz (±10%)	0.17 A
3 AC 400 V / 60 Hz (±10%)	0.22 A
3 AC 480 V / 60 Hz (±10%)	0.22 A

¹⁾ at a rated frequency of 4 kHz and a speed range of up to 5000 rpm

Physical constants

Thermal time constant	35 min
Moment of inertia	2,320 kgcm ²
Weight (approx.)	230 kg

Connection

Type of electrical connection	Terminal box
Position of the connection	NDE top
Power connection	right
Signal connection	DE
Terminal box designation	gk863

Cooling data and sound pressure level

Airflow, min.	0.16 m ³ /s
Sound pressure level L _{pA} (1m) motor + external fan operation 50 HZ rated load, tolerance + 3dB	73 dB ¹⁾
Air discharge	axial
Pressure drop	200 Pa