



Figure similar

Data sheet for SIMOTICS M-1PH8

Article No. : 1PH8165-1UD13-2LC1

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data

		P _N [kW]	M _N [Nm]	I _N [A]	U _N [V]	f _N [Hz]	n _N [rpm]	M _{max} [Nm]	I _{max} [A]	n _{max} [rpm]	M ₀ [Nm]	I ₀ [A]	η	cos φ	I _μ [A]
Y	ALM 400V	31.0	257.0	69.0	333	39.2	1,150	740	192.0	9,000	302.0	77	0.921	0.89	20.9
	BLM/SLM 400V	28.0	267.0	71.0	292	34.2	1,000	740	192.0	9,000	302.0	77	0.914	0.89	22.2
	ALM/BLM/SLM 480V	34.0	241.0	66.0	387	45.8	1,350	740	192.0	9,000	302.0	77	0.928	0.86	22.5

Mechanical data

Motor type	Squirrel cage asynchronous motor
Shaft height	160
Cooling	Forced ventilation NDE -> DE
Vibration severity grade	SPECIAL/B
Shaft and flange accuracy	SPECIAL
Degree of protection	IP55
Design acc. to Code I	IM B35 (IM V15, IM V35)
Temperature monitoring	Pt1000 temperature sensor in the stator winding
Color	Standard (Anthracite RAL 7016)
Type of the bearing	Performance
Shaft extension	Feather key with half key balancing
Encoder system	Incremental encoder 20 bit without commutation position (encoder IN20DQ)

Physical constants

Thermal time constant	35 min
Moment of inertia	2,320 kgcm ²
Weight (approx.)	230 kg

Connection

Type of electrical connection	Terminal box
Position of the connection	NDE top
Power connection	NDE
Signal connection	left
Terminal box designation	gk863

Cooling data and sound pressure level

Airflow, min.	0.16 m ³ /s
Sound pressure level LpA(1m) motor + external fan operation 50 HZ rated load, tolerance + 3dB	73 dB ¹⁾
Air discharge	axial
Pressure drop	200 Pa

¹⁾ at a rated frequency of 4 kHz and a speed range of up to 5000 rpm