



Figure similar

Data sheet for SIMOTICS M-1PH8

Article No. : 1PH8165-2DF10-1BC1

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data

		P _N [kW]	M _N [Nm]	I _N [A]	U _N [V]	f _N [Hz]	n _N [rpm]	M _{max} [Nm]	I _{max} [A]	n _{max} [rpm]	M ₀ [Nm]	I ₀ [A]	η	cos φ	I _μ [A]
Y	ALM 400V	69.0	375.0	115.0	395	117.0	1,750	1,135	367.0	4,000	440.0	126	0.943	0.000	0.0
	BLM/SLM 400V	61.0	390.0	119.0	340	100.0	1,500	1,135	367.0	4,000	440.0	126	0.940	0.000	0.0
	ALM/BLM/SLM 480V	74.0	355.0	110.0	445	133.0	2,000	1,135	367.0	4,000	440.0	126	0.946	0.000	0.0

Mechanical data

Motor type	Permanent-magnet synchronous motor
Shaft height	160
Cooling	Forced ventilation NDE -> DE
Vibration severity grade	R/A
Shaft and flange accuracy	R
Degree of protection	IP55
Design acc. to Code I	IM B3 (IM V5, IM V6, IM B6, IM B7, IM B8)
Temperature monitoring	Pt1000 temperature sensor in the stator winding
Color	Standard (Anthracite RAL 7016)
Type of the bearing	Standard with fixed bearing
Shaft extension	Feather key with full key balancing
Encoder system	Incremental encoder 22 bit with commutation position 11 bit, max. encoder speed = 12000 rpm

Physical constants

Thermal time constant	10 min
Moment of inertia	2,160 kgcm ²
Weight (approx.)	218 kg

Connection

Type of electrical connection	Terminal box
Position of the connection	NDE top
Power connection	NDE
Signal connection	left
Terminal box designation	gk874

Cooling data and sound pressure level

Airflow, min.	0.16 m ³ /s
Sound pressure level LpA(1m) motor + external fan operation 50 HZ rated load, tolerance + 3dB	73 dB ¹⁾
Air discharge	axial
Pressure drop	200 Pa

¹⁾at a rated frequency of 4 kHz and a speed range of up to 5000 rpm