



Figure similar

Data sheet for SIMOTICS M-1PH8

Article No. : 1PH8165-2FF02-2BA1

Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :

Engineering data

|   |                  | P <sub>N</sub><br>[kW] | M <sub>N</sub><br>[Nm] | I <sub>N</sub><br>[A] | U <sub>N</sub><br>[V] | f <sub>N</sub><br>[Hz] | n <sub>N</sub><br>[rpm] | M <sub>max</sub><br>[Nm] | I <sub>max</sub><br>[A] | n <sub>max</sub><br>[rpm] | M <sub>0</sub><br>[Nm] | I <sub>0</sub><br>[A] | η     | cos φ | I <sub>μ</sub><br>[A] |
|---|------------------|------------------------|------------------------|-----------------------|-----------------------|------------------------|-------------------------|--------------------------|-------------------------|---------------------------|------------------------|-----------------------|-------|-------|-----------------------|
| Y | ALM 400V         | 69.0                   | 375.0                  | 115.0                 | 395                   | 117.0                  | 1,750                   | 1,135                    | 367.0                   | 4,000                     | 440.0                  | 126                   | 0.943 | 0.00  | 0.0                   |
|   | BLM/SLM 400V     | 61.0                   | 390.0                  | 119.0                 | 340                   | 100.0                  | 1,500                   | 1,135                    | 367.0                   | 4,000                     | 440.0                  | 126                   | 0.940 | 0.00  | 0.0                   |
|   | ALM/BLM/SLM 480V | 74.0                   | 355.0                  | 110.0                 | 445                   | 133.0                  | 2,000                   | 1,135                    | 367.0                   | 4,000                     | 440.0                  | 126                   | 0.946 | 0.00  | 0.0                   |

Mechanical data

|                           |                                                                                      |
|---------------------------|--------------------------------------------------------------------------------------|
| Motor type                | Permanent-magnet synchronous motor                                                   |
| Shaft height              | 160                                                                                  |
| Cooling                   | Forced ventilation DE -> NDE                                                         |
| Vibration severity grade  | R/A                                                                                  |
| Shaft and flange accuracy | R                                                                                    |
| Degree of protection      | IP55                                                                                 |
| Design acc. to Code I     | IM B5 (IM V1, IM V3)                                                                 |
| Temperature monitoring    | Pt1000 temperature sensor in the stator winding                                      |
| Color                     | Standard (Anthracite RAL 7016)                                                       |
| Type of the bearing       | Standard with fixed bearing                                                          |
| Shaft extension           | Feather key with half key balancing                                                  |
| Encoder system            | Absolut encoder 22 bit Singleturn + 12 bit Multiturn, max. encoder speed = 12000 rpm |

Physical constants

|                       |                         |
|-----------------------|-------------------------|
| Thermal time constant | 10 min                  |
| Moment of inertia     | 2,160 kgcm <sup>2</sup> |
| Weight (approx.)      | 218 kg                  |

Connection

|                               |              |
|-------------------------------|--------------|
| Type of electrical connection | Terminal box |
| Position of the connection    | NDE top      |
| Power connection              | right        |
| Signal connection             | DE           |
| Terminal box designation      | gk874        |

Cooling data and sound pressure level

|                                                                                               |                        |
|-----------------------------------------------------------------------------------------------|------------------------|
| Airflow, min.                                                                                 | 0.16 m <sup>3</sup> /s |
| Sound pressure level LpA(1m) motor + external fan operation 50 HZ rated load, tolerance + 3dB | 73 dB <sup>1)</sup>    |
| Air discharge                                                                                 | axial                  |
| Pressure drop                                                                                 | 200 Pa                 |

<sup>1)</sup> at a rated frequency of 4 kHz and a speed range of up to 5000 rpm