



Figure similar

Data sheet for SIMOTICS M-1PH8

Article No. : 1PH8184-1DL05-2BB1-Z
X01

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data

		P _N [kW]	M _N [Nm]	I _N [A]	U _N [V]	f _N [Hz]	n _N [rpm]	M _{max} [Nm]	I _{max} [A]	n _{max} [rpm]	M ₀ [Nm]	I ₀ [A]	η	cos φ	l _μ [A]
Y	ALM 400V	81.0	267.0	152.0	395	97.3	2,900	730	380.0	5,000	267.0	152	0.952	0.82	76.0
	BLM/SLM 400V	78.0	298.0	166.0	340	84.0	2,500	730	380.0	5,000	298.0	166	0.952	0.84	75.0
	ALM/BLM/SLM 480V	65.0	183.0	120.0	460	113.7	3,400	730	380.0	5,000	183.0	120	0.944	0.72	77.0

Mechanical data

Motor type	Squirrel cage asynchronous motor
Shaft height	180
Cooling	Forced ventilation DE -> NDE
Vibration severity grade	R/A
Shaft and flange accuracy	R
Degree of protection	IP55
Design acc. to Code I	IM V15 with A450 flange
Temperature monitoring	Pt1000 temperature sensor in the stator winding
Color	Jet black, matt RAL 9005
Type of the bearing	Standard
Shaft extension	Feather key with half key balancing
Encoder system	Incremental encoder 22 bit with commutation position 11 bit, max. encoder speed = 12000 rpm

Physical constants

Thermal time constant	22 min
Moment of inertia	4,890 kgcm²
Weight (approx.)	350 kg

Connection

Type of electrical connection	Terminal box
Position of the connection	NDE top
Power connection	left
Signal connection	DE
Terminal box designation	1XB7322-P05

Cooling data and sound pressure level

Airflow, min.	0.17 m³/s
Sound pressure level LpA(1m) motor + external fan operation 50 HZ rated load, tolerance + 3dB	73 dB ¹⁾
Air discharge	axial
Pressure drop	550 Pa

Special design

X01 Paint finish: Jet black, matt RAL 9005

¹⁾ at a rated frequency of 2 kHz and a speed range of up to 5000 rpm