



Figure similar

## Data sheet for SIMOTICS M-1PH8

Article No. : 1PH8186-1DC00-0BA1

Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :

### Engineering data

		$P_N$ [kW]	$M_N$ [Nm]	$I_N$ [A]	$U_N$ [V]	$f_N$ [Hz]	$n_N$ [rpm]	$M_{max}$ [Nm]	$I_{max}$ [A]	$n_{max}$ [rpm]	$M_0$ [Nm]	$I_0$ [A]	$\eta$	$\cos \phi$	$I\mu$ [A]
Y	ALM 400V	40.0	478.0	83.0	360	27.3	800	1,230	205.0	5,000	478.0	83	0.916	0.84	41.0
	BLM/SLM 400V	35.0	478.0	83.0	330	23.9	700	1,230	205.0	5,000	478.0	83	0.909	0.81	44.0
	ALM/BLM/SLM 480V	50.0	478.0	83.0	450	33.9	1,000	1,230	205.0	5,000	478.0	83	0.929	0.83	42.0

### Mechanical data

Motor type	Squirrel cage asynchronous motor
Shaft height	180
Cooling	Forced ventilation DE -> NDE
Vibration severity grade	R/A
Shaft and flange accuracy	R
Degree of protection	IP55
Design acc. to Code I	IM B3 (IM B6, IM B7, IM B8, IM V6)
Temperature monitoring	Pt1000 temperature sensor in the stator winding
Color	Standard (Anthracite RAL 7016)
Type of the bearing	Standard
Shaft extension	Plain shaft
Encoder system	Incremental encoder 22 bit with commutation position 11 bit, max. encoder speed = 12000 rpm

### Physical constants

Thermal time constant	25 min
Moment of inertia	6,520 kgcm <sup>2</sup>
Weight (approx.)	422 kg

### Connection

Type of electrical connection	Terminal box
Position of the connection	NDE top
Power connection	right
Signal connection	DE
Terminal box designation	1XB7322-P05

### Cooling data and sound pressure level

Airflow, min.	0.17 m <sup>3</sup> /s
Sound pressure level LpA(1m) motor + external fan operation 50 HZ rated load, tolerance + 3dB	73 dB <sup>1)</sup>
Air discharge	axial
Pressure drop	550 Pa

<sup>1)</sup> at a rated frequency of 2 kHz and a speed range of up to 5000 rpm