

Data sheet for SIMOTICS M-1PH8

Article No. : **1PH8186-1EL00-0BA2-Z**
K18+K40



Figure similar

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data

		P _N [kW]	M _N [Nm]	I _N [A]	U _N [V]	f _N [Hz]	n _N [rpm]	M _{max} [Nm]	I _{max} [A]	n _{max} [rpm]	M ₀ [Nm]	I ₀ [A]	η	cos φ	I _μ [A]
Y	ALM 400V	101.0	333.0	198.0	385	97.2	2,900	920	480.0	5,000	333.0	198	0.954	0.80	106.0
	BLM/SLM 400V	106.0	405.0	230.0	335	83.9	2,500	920	480.0	5,000	405.0	230	0.955	0.84	107.0
	ALM/BLM/SLM 480V	81.0	228.0	158.0	455	113.7	3,400	920	480.0	5,000	228.0	158	0.943	0.69	109.0

Mechanical data

Motor type	Squirrel cage asynchronous motor
Shaft height	180
Cooling	Forced ventilation DE -> NDE
Vibration severity grade	R/A
Shaft and flange accuracy	R
Degree of protection	IP55
Design acc. to Code I	IM B3 (IM B6, IM B7, IM B8, IM V6)
Temperature monitoring	Pt1000 temperature sensor in the stator winding
Color	Standard (Anthracite RAL 7016)
Type of the bearing	Standard
Shaft extension	Plain shaft
Encoder system	Absolut encoder EnDat 2048 S/R, max. encoder speed = 12000 rpm

Physical constants

Thermal time constant	25 min
Moment of inertia	6,520 kgcm ²
Weight (approx.)	422 kg

Connection

Type of electrical connection	Terminal box
Position of the connection	NDE top
Power connection	right
Signal connection	DE
Terminal box designation	1XB7422-P06

Cooling data and sound pressure level

Airflow, min.	0.17 m ³ /s
Sound pressure level LpA(1m) motor + external fan operation 50 HZ rated load, tolerance + 3dB	73 dB ¹⁾
Air discharge	axial
Pressure drop	550 Pa

Special design

K18	Radial shaft sealing ring DE
K40	Regreasing system

¹⁾ at a rated frequency of 2 kHz and a speed range of up to 5000 rpm