



Figure similar

Data sheet for SIMOTICS M-1PH8

Article No. : 1PH8186-1HF12-2BD1-Z
K40+L00+M39

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data

		P _N [kW]	M _N [Nm]	I _N [A]	U _N [V]	f _N [Hz]	n _N [rpm]	M _{max} [Nm]	I _{max} [A]	n _{max} [rpm]	M ₀ [Nm]	I ₀ [A]	η	cos φ	l _μ [A]
Y	ALM 400V	85.0	464.0	164.0	385	58.9	1,750	1,230	400.0	5,000	464.0	164	0.949	0.82	83.0
	BLM/SLM 400V	74.0	471.0	166.0	330	50.6	1,500	1,230	400.0	5,000	471.0	166	0.945	0.83	82.0
	ALM/BLM/SLM 480V	94.0	449.0	160.0	445	67.2	2,000	1,230	400.0	5,000	449.0	160	0.952	0.80	86.0

Mechanical data

Motor type	Squirrel cage asynchronous motor
Shaft height	180
Cooling	Forced ventilation NDE -> DE
Vibration severity grade	R/A
Shaft and flange accuracy	R
Degree of protection	IP55
Design acc. to Code I	IM B5 with A450 flange (IM V3)
Temperature monitoring	KTY84 temperature sensor in the stator winding
Color	Standard (Anthracite RAL 7016)
Type of the bearing	Standard
Shaft extension	Feather key with half key balancing
Encoder system	Incremental encoder HTL 1024 S/R, max. encoder speed = 9000 rpm

Physical constants

Thermal time constant	25 min
Moment of inertia	6,520 kgcm ²
Weight (approx.)	422 kg

Connection

Type of electrical connection	Terminal box
Position of the connection	NDE top
Power connection	DE
Signal connection	right
Terminal box designation	1XB7422-P06

Cooling data and sound pressure level

Airflow, min.	0.17 m ³ /s
Sound pressure level LpA(1m) motor + external fan operation 50 HZ rated load, tolerance + 3dB	73 dB ¹⁾
Air discharge	axial
Pressure drop	550 Pa

Special design

K40	Regreasing system
L00	Terminal box replaced by the next larger terminal box
M39	Version for Zone 22 hazardous areas according to EN 50281/IEC 61241

¹⁾ at a rated frequency of 2 kHz and a speed range of up to 5000 rpm