



Figure similar

Data sheet for SIMOTICS M-1PH8

Article No. : 1PH8224-1HD40-2EA2-Z
K10+K40

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data

		P _N [kW]	M _N [Nm]	I _N [A]	U _N [V]	f _N [Hz]	n _N [rpm]	M _{max} [Nm]	I _{max} [A]	n _{max} [rpm]	M ₀ [Nm]	I ₀ [A]	η	cos φ	l _μ [A]
Y	ALM 400V	120.0	997.0	220.0	385	39.1	1,150	1,760	385.0	4,500	997.0	220	0.934	0.88	74.0
	BLM/SLM 400V	105.0	1,003.0	220.0	335	34.1	1,000	1,760	385.0	4,500	1,003.0	2,200	0.926	0.88	73.0
	ALM/BLM/SLM 480V	137.0	969.0	215.0	450	45.7	1,350	1,760	385.0	4,500	969.0	215	0.941	0.87	75.0

Mechanical data

Motor type	Squirrel cage asynchronous motor
Shaft height	225
Cooling	Open circuit cooling NDE-> DE
Vibration severity grade	A
Shaft and flange accuracy	N
Degree of protection	IP23
Design acc. to Code I	IM B3 (IM B6, IM B7, IM B8, IM V6)
Temperature monitoring	Pt1000 temperature sensor in the stator winding
Color	Standard (Anthracite RAL 7016)
Type of the bearing	Increased cantilever forces
Shaft extension	Feather key with half key balancing
Encoder system	Incremental encoder HTL 1024 S/R, max. encoder speed = 9000 rpm

Physical constants

Thermal time constant	21 min
Moment of inertia	14,800 kgcm ²
Weight (approx.)	610 kg

Connection

Type of electrical connection	Terminal box
Position of the connection	NDE left
Power connection	DE
Signal connection	top
Terminal box designation	1XB7422-P06

Cooling data and sound pressure level

Airflow, min.	0.33 m³/s
Sound pressure level LpA(1m) motor + external fan operation 50 HZ rated load, tolerance + 3dB	73 dB ¹⁾
Air discharge	axial
Pressure drop	600 Pa

Special design

- K10 Terminal box NDE left
- K40 Regreasing system

¹⁾ at a rated frequency of 2 kHz and a speed range of up to 2000 rpm