



Figure similar

Data sheet for SIMOTICS M-1PH8

Article No. : 1PH8226-1HF03-2AA2

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data

		P _N [kW]	M _N [Nm]	I _N [A]	U _N [V]	f _N [Hz]	n _N [rpm]	M _{max} [Nm]	I _{max} [A]	n _{max} [rpm]	M ₀ [Nm]	I ₀ [A]	η	cos φ	I _μ [A]
Y	ALM 400V	135.0	737.0	250.0	395	58.8	1,750	1,850	570.0	4,500	737.0	250	0.960	0.830	119.0
	BLM/SLM 400V	130.0	828.0	270.0	340	50.5	1,500	1,850	570.0	4,500	828.0	270	0.957	0.850	119.0
	ALM/BLM/SLM 480V	135.0	731.0	245.0	450	67.1	2,000	1,850	570.0	4,500	731.0	245	0.961	0.830	119.0

Mechanical data

Motor type	Squirrel cage asynchronous motor
Shaft height	225
Cooling	Forced ventilation DE -> NDE
Vibration severity grade	A
Shaft and flange accuracy	N
Degree of protection	IP55
Design acc. to Code I	IM B35 with A550 flange (IM V35)
Temperature monitoring	Pt1000 temperature sensor in the stator winding
Color	Standard (Anthracite RAL 7016)
Type of the bearing	Standard
Shaft end	Feather key with half key balancing
Encoder system	Incremental encoder HTL 1024 S/R, max. encoder speed = 9000 rpm

¹⁾ at a rated frequency of 2 kHz and a speed range of up to 3500 rpm

Physical constants

Thermal time constant	52 min
Moment of inertia	19,300 kgcm ²
Weight (approx.)	740 kg

Connection

Type of electrical connection	Terminal box
Position of the connection	NDE top
Power connection	right
Signal connection	DE
Terminal box designation	1XB7422-P06

Cooling data and sound pressure level

Airflow, min.	0.31 m³/s
Sound pressure level LpA(1m) motor + external fan operation 50 HZ rated load, tolerance + 3dB	73 dB ¹⁾
Air discharge	axial
Pressure drop	650 Pa

External fan

Max. power consumption	
1 AC 200 ... 277 V (±10%) 50/60 Hz ±10%	2.0 ... 2.3 A