



Figure similar

Data sheet for SIMOTICS M-1PH8

Article No. : 1PH8226-1HF20-2CB1-Z
K40+P01+X14

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data

		P _N [kW]	M _N [Nm]	I _N [A]	U _N [V]	f _N [Hz]	n _N [rpm]	M _{max} [Nm]	I _{max} [A]	n _{max} [rpm]	M ₀ [Nm]	I ₀ [A]	η	cos φ	I _μ [A]
Y	ALM 400V	169.0	922.0	295.0	390	58.8	1,750	1,845	590.0	4,500	922.0	295	0.895	0.880	116.0
	BLM/SLM 400V	145.0	923.0	295.0	340	50.5	1,500	1,846	590.0	4,500	923.0	295	0.957	0.870	119.0
	ALM/BLM/SLM 480V	191.0	912.0	290.0	450	67.1	2,000	1,824	580.0	4,500	912.0	290	0.961	0.880	118.0

Mechanical data

Motor type	Squirrel cage asynchronous motor
Shaft height	225
Cooling	Water cooling
Vibration severity grade	S/A
Shaft and flange accuracy	R
Degree of protection	IP55
Design acc. to Code I	IM B3 (IM B6, IM B7, IM B8, IM V6)
Temperature monitoring	KTY84 temperature sensor in the stator winding
Color	Traffic blue RAL 5017
Type of the bearing	Standard
Shaft extension	Feather key with half key balancing
Encoder system	Incremental encoder HTL 1024 S/R, max. encoder speed = 9000 rpm

Physical constants

Thermal time constant	32 min
Moment of inertia	18,950 kgcm ²
Weight (approx.)	740 kg

Connection

Type of electrical connection	Terminal box
Position of the connection	NDE top
Power connection	left
Signal connection	DE
Terminal box designation	1XB7700-P02

Cooling data and sound pressure level

Flow rate, min.	20 l/min
Sound pressure level LpA(1m) motor rated load, tolerance + 3dB	70 dB ¹⁾
Pressure drop	0.6 bar
NDE thread connection	0.375 Inches

Cooling water specification

pH value	6 ... 9
Total hardness	1.7 mmol/l
Electrical conductivity	2,000 μS/cm
Chloride ions	250 mg/l
Sulfate ions	240 mg/l
Nitrate ions	50 mg/l
Dissolved substances	340 mg/l
Maximum particle size	100 μm
Antifreeze/corrosion protection	20 ... 30 %

Special design

K40	Regreasing system
P01	Cable entry plate 3 x M63 x 1.5
X14	Paint finish: Traffic blue RAL 5017

¹⁾at a rated frequency of 2 kHz or 4 kHz and a speed range of up to 4500 rpm