



Figure similar

Data sheet for SIMOTICS M-1PH8

Article No. : 1PH8226-1HF40-2EA1-Z
A12+G14+K09+K40+K85

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data

		P _N [kW]	M _N [Nm]	I _N [A]	U _N [V]	f _N [Hz]	n _N [rpm]	M _{max} [Nm]	I _{max} [A]	n _{max} [rpm]	M ₀ [Nm]	I ₀ [A]	η	cos φ	I _μ [A]
Y	ALM 400V	200.0	1,091.0	350.0	390	59.0	1,750	1,850	580.0	4,500	1,091.0	350	0.954	0.89	114.0
	BLM/SLM 400V	175.0	1,114.0	350.0	340	50.7	1,500	1,850	580.0	4,500	1,114.0	350	0.950	0.89	117.0
	ALM/BLM/SLM 480V	220.0	1,051.0	335.0	450	67.3	2,000	1,850	580.0	4,500	1,051.0	335	0.957	0.88	117.0

Mechanical data

Motor type	Squirrel cage asynchronous motor
Shaft height	225
Cooling	Open circuit cooling NDE-> DE
Vibration severity grade	A
Shaft and flange accuracy	N
Degree of protection	IP23
Design acc. to Code I	IM B3 (IM B6, IM B7, IM B8, IM V6)
Temperature monitoring	KTY84 temperature sensor in the stator winding
Color	Standard (Anthracite RAL 7016)
Type of the bearing	Increased cantilever forces
Shaft extension	Feather key with half key balancing
Encoder system	Incremental encoder HTL 1024 S/R, max. encoder speed = 9000 rpm

Physical constants

Thermal time constant	23 min
Moment of inertia	19,300 kgcm ²
Weight (approx.)	740 kg

Connection

Type of electrical connection	Terminal box
Position of the connection	NDE right
Power connection	NDE
Signal connection	below
Terminal box designation	1XB7700-P02

Cooling data and sound pressure level

Airflow, min.	0.33 m³/s
Sound pressure level LpA(1m) motor + external fan operation 50 HZ rated load, tolerance + 3dB	73 dB ¹⁾
Air discharge	axial
Pressure drop	600 Pa

Special design

A12	Additional PTC thermistor chain for alarm and tripping
G14	with air filter
K09	Terminal box NDE right
K40	Regreasing system
K85	Terminal box rotated through +180 degrees

¹⁾ at a rated frequency of 2 kHz and a speed range of up to 2000 rpm