

Data sheet for SIMOTICS M-1PH8

Article No. : 1PH8226-2MF12-2BD1



Figure similar

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data

		P _N [kW]	M _N [Nm]	I _N [A]	U _N [V]	f _N [Hz]	n _N [rpm]	M _{max} [Nm]	I _{max} [A]	n _{max} [rpm]	M ₀ [Nm]	I ₀ [A]	η	cos φ	I _μ [A]
Y	ALM 400V	156.0	851.0	295.0	335	117.0	1,750	3,200	1,120.0	3,500	944.0	320	0.966	0.00	0.0
	BLM/SLM 400V	134.0	853.0	295.0	288	100.0	1,500	3,200	1,120.0	3,500	944.0	320	0.967	0.00	0.0
	ALM/BLM/SLM 480V	157.0	750.0	260.0	378	133.0	2,000	3,200	1,120.0	3,500	944.0	320	0.964	0.00	0.0

Mechanical data	
Motor type	Permanent-magnet synchronous motor
Shaft height	225
Cooling	Forced ventilation NDE -> DE
Vibration severity grade	R/A
Shaft and flange accuracy	R
Degree of protection	IP55
Design acc. to Code I	IM B5 with A550 flange (IM V3)
Temperature monitoring	KTY84 temperature sensor in the stator winding
Color	Standard (Anthracite RAL 7016)
Type of the bearing	Standard
Shaft extension	Feather key with half key balancing
Encoder system	Incremental encoder sin/cos 1Vpp 2048 S/R with C- and D-Spur, max. encoder speed = 12000 rpm

Physical constants	
Thermal time constant	26 min
Moment of inertia	16,600 kgcm ²
Weight (approx.)	700 kg

Connection	
Type of electrical connection	Terminal box
Position of the connection	NDE top
Power connection	DE
Signal connection	right
Terminal box designation	1XB7700-P02

Cooling data and sound pressure level	
Airflow, min.	0.31 m ³ /s
Sound pressure level LpA(1m) motor + external fan operation 50 HZ rated load, tolerance + 3dB	73 dB ¹⁾
Air discharge	axial
Pressure drop	650 Pa

¹⁾ at a rated frequency of 2 kHz and a speed range of up to 3500 rpm