



Figure similar

Data sheet for SIMOTICS M-1PH8

Article No. : 1PH8228-1DD00-1LB1-Z
K40

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data

		P _N [kW]	M _N [Nm]	I _N [A]	U _N [V]	f _N [Hz]	n _N [rpm]	M _{max} [Nm]	I _{max} [A]	n _{max} [rpm]	M ₀ [Nm]	I ₀ [A]	η	cos φ	l _μ [A]
Y	ALM 400V	129.0	1,071.0	235.0	390	38.8	1,150	2,750	570.0	6,000	1,071.0	235	0.953	0.86	97.0
	BLM/SLM 400V	113.0	1,079.0	235.0	340	33.9	1,000	2,750	570.0	6,000	1,079.0	235	0.948	0.87	97.0
	ALM/BLM/SLM 480V	147.0	1,040.0	225.0	460	45.5	1,350	2,750	570.0	6,000	1,040.0	225	0.957	0.86	99.0

Mechanical data

Motor type	Squirrel cage asynchronous motor
Shaft height	225
Cooling	Forced ventilation DE -> NDE
Vibration severity grade	SR/A
Shaft and flange accuracy	R
Degree of protection	IP55
Design acc. to Code I	IM B3 (IM B6, IM B7, IM B8, IM V6)
Temperature monitoring	Pt1000 temperature sensor in the stator winding
Color	Standard (Anthracite RAL 7016)
Type of the bearing	Performance
Shaft extension	Feather key with full key balancing
Encoder system	Incremental encoder 22 bit with commutation position 11 bit, max. encoder speed = 12000 rpm

Physical constants

Thermal time constant	55 min
Moment of inertia	23,300 kgcm ²
Weight (approx.)	870 kg

Connection

Type of electrical connection	Terminal box
Position of the connection	NDE top
Power connection	left
Signal connection	DE
Terminal box designation	1XB7422-P06

Cooling data and sound pressure level

Airflow, min.	0.31 m³/s
Sound pressure level LpA(1m) motor + external fan operation 50 HZ rated load, tolerance + 3dB	73 dB ¹⁾
Air discharge	axial
Pressure drop	650 Pa

Special design

K40 Regreasing system

¹⁾ at a rated frequency of 2 kHz and a speed range of up to 3500 rpm