



Figure similar

Data sheet for SIMOTICS M-1PH8

Article No. : 1PH8228-1JF43-2BA2-Z  
K09+K83

Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :

Engineering data

|   |                  | P <sub>N</sub><br>[kW] | M <sub>N</sub><br>[Nm] | I <sub>N</sub><br>[A] | U <sub>N</sub><br>[V] | f <sub>N</sub><br>[Hz] | n <sub>N</sub><br>[rpm] | M <sub>max</sub><br>[Nm] | I <sub>max</sub><br>[A] | n <sub>max</sub><br>[rpm] | M <sub>0</sub><br>[Nm] | I <sub>0</sub><br>[A] | η     | cos φ | I <sub>μ</sub><br>[A] |
|---|------------------|------------------------|------------------------|-----------------------|-----------------------|------------------------|-------------------------|--------------------------|-------------------------|---------------------------|------------------------|-----------------------|-------|-------|-----------------------|
| Y | ALM 400V         | 265.0                  | 1,446.0                | 460.0                 | 390                   | 59.0                   | 1,750                   | 2,450                    | 760.0                   | 4,500                     | 1,446.0                | 460                   | 0.956 | 0.890 | 162.0                 |
|   | BLM/SLM 400V     | 230.0                  | 1,464.0                | 465.0                 | 340                   | 50.6                   | 1,500                   | 2,450                    | 760.0                   | 4,500                     | 1,464.0                | 465                   | 0.953 | 0.880 | 166.0                 |
|   | ALM/BLM/SLM 480V | 288.0                  | 1,375.0                | 440.0                 | 450                   | 67.3                   | 2,000                   | 2,450                    | 760.0                   | 4,500                     | 1,375.0                | 440                   | 0.959 | 0.880 | 166.0                 |

Mechanical data

|                           |                                                                 |
|---------------------------|-----------------------------------------------------------------|
| Motor type                | Squirrel cage asynchronous motor                                |
| Shaft height              | 225                                                             |
| Cooling                   | Open circuit cooling NDE-> DE                                   |
| Vibration severity grade  | R/A                                                             |
| Shaft and flange accuracy | R                                                               |
| Degree of protection      | IP23                                                            |
| Design acc. to Code I     | IM B35 with A550 flange (IM V35)                                |
| Temperature monitoring    | Pt1000 temperature sensor in the stator winding                 |
| Color                     | Standard (Anthracite RAL 7016)                                  |
| Type of the bearing       | Standard                                                        |
| Shaft end                 | Feather key with half key balancing                             |
| Encoder system            | Incremental encoder HTL 2048 S/R, max. encoder speed = 4600 rpm |

Physical constants

|                       |                          |
|-----------------------|--------------------------|
| Thermal time constant | 25 min                   |
| Moment of inertia     | 23,300 kgcm <sup>2</sup> |
| Weight (approx.)      | 870 kg                   |

Connection

|                               |              |
|-------------------------------|--------------|
| Type of electrical connection | Terminal box |
| Position of the connection    | NDE right    |
| Power connection              | top          |
| Signal connection             | NDE          |
| Terminal box designation      | 1XB7700-P02  |

Cooling data and sound pressure level

|                                                                                               |                     |
|-----------------------------------------------------------------------------------------------|---------------------|
| Airflow, min.                                                                                 | 0.33 m³/s           |
| Sound pressure level LpA(1m) motor + external fan operation 50 HZ rated load, tolerance + 3dB | 73 dB <sup>1)</sup> |
| Air discharge                                                                                 | axial               |
| Pressure drop                                                                                 | 600 Pa              |

External fan

Max. power consumption

1 AC 200 ... 277 V (±10%) 50/60 Hz    2.0 ... 2.3 A  
±10%

Special design

K09    Terminal box NDE right  
K83    Terminal box rotated through +90 degrees

<sup>1)</sup> at a rated frequency of 2 kHz and a speed range of up to 2000 rpm