



Data sheet for SIMOTICS M-1PH8

Article No. : 1PH8288-1EF20-2BA2

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data															
		P _N [kW]	M _N [Nm]	I _N [A]	U _N [V]	f _N [Hz]	n _N [rpm]	M _{max} [Nm]	I _{max} [A]	n _{max} [rpm]	M ₀ [Nm]	I ₀ [A]	η	cos φ	I _μ [A]
Δ	ALM 400V	403.0	2,199.0	670.0	400	58.7	1,750	5,498	1,675.0	3,300	2,199.0	670	0.968	0.900	232.0
	BLM/SLM 400V	345.0	2,197.0	660.0	345	50.3	1,500	5,491	1,650.0	3,300	2,197.0	660	0.967	0.900	234.0
	ALM/BLM/SLM 480V	460.0	2,197.0	670.0	455	67.0	2,000	5,491	1,675.0	3,300	2,197.0	670	0.969	0.900	230.0

Mechanical data	
Motor type	Squirrel cage asynchronous motor
Shaft height	280
Cooling	Water cooling
Vibration severity grade	R/A
Shaft and flange accuracy	R
Degree of protection	IP55
Design acc. to Code I	IM B3 (IM V6)
Temperature monitoring	Pt1000 temperature sensor in the stator winding
Color	Standard (Anthracite RAL 7016)
Type of the bearing	Standard
Shaft end	Feather key with half key balancing
Encoder system	Absolut encoder EnDat 2048 S/R, max. encoder speed = 12000 rpm

Physical constants	
Thermal time constant	35 min
Moment of inertia	63,000 kgcm ²
Weight (approx.)	1,750 kg

Connection	
Type of electrical connection	Terminal box
Position of the connection	NDE top
Power connection	right
Signal connection	DE
Terminal box designation	1XB7712-P03

Cooling data and sound pressure level	
Flow rate, min.	35 l/min
Sound pressure level L _{pA} (1m) motor rated load, tolerance + 3dB	72 dB ¹⁾
Pressure drop	0.6 bar
NDE thread connection	0.5 Inches

Cooling water specification	
pH value	6 ... 9
Total hardness	1.7 mmol/l
Electrical conductivity	2,000 μS/cm
Chloride ions	250 mg/l
Sulfate ions	240 mg/l
Nitrate ions	50 mg/l
Dissolved substances	340 mg/l
Maximum particle size	100 μm
Antifreeze/corrosion protection	20 ... 30 %

¹⁾ at a rated frequency of 2 kHz and a speed range of up to 3300 rpm