

Data sheet for SIMOTICS M-1PH8

Article No. : 1PH8288-1HF10-2AV1



Figure similar

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data

		P _N [kW]	M _N [Nm]	I _N [A]	U _N [V]	f _N [Hz]	n _N [rpm]	M _{max} [Nm]	I _{max} [A]	n _{max} [rpm]	M ₀ [Nm]	I ₀ [A]	η	cos φ	I _μ [A]
Δ	ALM 400V	340.0	1,856.0	580.0	400	58.7	1,750	5,500	1,640.0	3,300	1,856.0	1,640	0.967	0.88	233.0
	BLM/SLM 400V	320.0	2,037.0	620.0	345	50.4	1,500	5,500	1,640.0	3,300	2,037.0	1,640	0.966	0.89	233.0
	ALM/BLM/SLM 480V	385.0	1,838.0	570.0	455	67.0	2,000	5,500	1,640.0	3,300	1,838.0	1,640	0.967	0.88	232.0

Mechanical data

Motor type	Squirrel cage asynchronous motor
Shaft height	280
Cooling	Forced ventilation NDE -> DE
Vibration severity grade	A
Shaft and flange accuracy	N
Degree of protection	IP55
Design acc. to Code I	IM B3 (IM V6)
Temperature monitoring	KTY84 temperature sensor in the stator winding
Color	Standard (Anthracite RAL 7016)
Type of the bearing	Standard
Shaft extension	Feather key with half key balancing
Encoder system	Incremental encoder HTL 1024 S/R, max. encoder speed = 9000 rpm

Physical constants

Thermal time constant	53 min
Moment of inertia	63,000 kgcm ²
Weight (approx.)	1,650 kg

Connection

Type of electrical connection	Terminal box
Position of the connection	NDE left
Power connection	below
Signal connection	DE
Terminal box designation	1XB7712-P03

Cooling data and sound pressure level

Airflow, min.	0.42 m ³ /s
Sound pressure level LpA(1m) motor + external fan operation 50 HZ rated load, tolerance + 3dB	74 dB ¹⁾
Air discharge	radial
Pressure drop	600 Pa

¹⁾ at a rated frequency of 2 kHz and a speed range of up to 3300 rpm