

ESB63-22N-07 Installation Contactor



Extended Product Type	ESB63-22N-07		
Product ID	1SAE351111R0722		
EAN	4013614519260		
Catalog Description	ESB63-22N-07 Installation Contactor		
Long Description	The ESB63..N installation contactors are used to control single and three-phase loads up to 63 A and can be operated by AC or DC.		
	These contactors are made for use in household applications as well as in industrial environments.		
	The following benefits are provided:		
	Hum-free operation, low power consumption and integrated overvoltage protection.		
	Various contact combinations and accessories are available.		

Package Level 1 EAN	4013614525575
Minimum Order Quantity	1 piece
Customs Tariff Number	85365080

Instructions and Manuals 2CDC103043M6801

Dimensions

Product Net Width	54 mm
Product Net Height	85 mm
Product Net Depth / Length	65 mm
Product Net Weight	0.405 kg

Technical

Rated Operational Voltage	Main Circuit 220 V DC Main Circuit 400 V AC
Rated Control Circuit Voltage (U_c)	400 V
Rated Frequency (f)	Control Circuit 400 Hz Control Circuit 50 Hz Control Circuit 60 Hz Control Circuit DC Main Circuit 50 Hz Main Circuit 60 Hz Main Circuit DC
Rated Operational Current AC-1 (I_e)	(NC) 30 A (NO) 63 A
Rated Operational Current AC-3 (I_e)	(230 V) Single Phase, NO 30 A
Rated Operational Power AC-1 (P_e)	(230 V) Single Phase, NC 6.9 kW (230 V) Single Phase, NO 14.5 kW
Rated Operational Power AC-3 (P_e)	(230 V) Single Phase, NO 5 kW
Rated Operational Current AC-7a (I_e)	(NO) 63 A
Rated Operational Power AC-7a (P_e)	(230 V) Single Phase, NC 6.9 kW (230 V) Single Phase, NO 14.5 kW
Rated Operational Current AC-7b (I_e)	(230 V) Single Phase, NO 30 A
Rated Operational Power AC-7b (P_e)	(230 V) Single Phase, NO 5 kW
Recommended Screw Driver	Control Circuit Pozidriv 1 Main Circuit Pozidriv 2
Rated Impulse Withstand Voltage (U_{imp})	6 kV
Rated Insulation Voltage (U_i)	500 V
Connecting Capacity Main Circuit	Flexible with Ferrule 1x 1.5 ... 16 mm ² Flexible with Ferrule 2x 1.5 ... 10 mm ² Flexible with Insulated Ferrule 1x 1.5 ... 16 mm ² Flexible with Insulated Ferrule 2x 1.5 ... 10 mm ² Flexible 2x 1.5 ... 10 mm ² Flexible 1x 1.5 ... 16 mm ² Rigid 1x 1.5 ... 25 mm ² Rigid 2x 1.5 ... 10 mm ²
Connecting Capacity Control Circuit	Flexible with Ferrule 1x 0.75 ... 2.5 mm ² Flexible with Ferrule 2x 0.75 ... 1.0 mm ² Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 2x 0.75 ... 1 mm ² Flexible 1x 1 ... 4.0 mm ² Flexible 2x 1 ... 2.5 mm ² Rigid 1x 1 ... 4 mm ² Rigid 2x 1 ... 2.5 mm ²
Tightening Torque	Control Circuit 0.9 N·m Main Circuit 2.5 N·m
Wire Stripping Length	Control Circuit 7 mm Main Circuit 13 mm
Degree of Protection	IP20
Electrical Durability	AC-1 (NO) 100000 cycle

	AC-3 (NO) 240000 cycle
	AC-7a (NO) 100000 cycle
	AC-7b (NO) 240000 cycle
Mechanical Durability	1000000 cycle
Number of Poles	4
Number of Main Contacts NC	2
Number of Main Contacts NO	2
Width in Number of Modular Spacings	3
Pollution Degree	3
Standards	IEC/EN 60947-1 IEC/EN 60947-4-1 IEC/EN 61095 UL 60947-1 UL 60947-4-1

Technical UL/CSA

Maximum Operating Voltage UL/CSA	Main Circuit 480 V AC
Horsepower Rating UL/CSA	(220 ... 240 V AC) Single Phase, NC 5 Hp (220 ... 240 V AC) Single Phase, NO 5 Hp (440 ... 480 V AC) Single Phase, NC 7.5 Hp (440 ... 480 V AC) Single Phase, NO 7.5 Hp
Connecting Capacity Main Circuit UL/CSA	Solid 16-4 AWG Stranded 16-4 AWG
Connecting Capacity Control Circuit UL/CSA	Solid 16-10 AWG Stranded 16-10 AWG
Tightening Torque UL/CSA	Control Circuit 8 in-lb Main Circuit 20 in-lb

Environmental

Ambient Air Temperature	Operation -25 ... +55 °C Storage -40 ... +80 °C
Maximum Operating Altitude Permissible	2000 m
Resistance to Shock acc. to IEC 60068-2-27	11 ms Pulse 15g
RoHS Status	Following EU Directive 2011/65/EU

Certificates and Declarations (Document Number)

ABS Certificate	1SAA920000-0101
CB Certificate	1SAA920005-2001
CQC Certificate	CQC2017010304993562 CQC2017010304993563
cULus Certificate	cUL_E191658
Declaration of Conformity - CCC	2020980304001310 2020980304001313
Declaration of Conformity - CE	1SAD938506-0302
Declaration of Conformity - UKCA	1SAD938500-1302
DNV Certificate	1SAA920000-0306
EAC Certificate	1SAA920001-2702
Environmental Information	1SAC200065H0009
Instructions and Manuals	2CDC103043M6801

RINA Certificate	1SAA920000-0801
RMRS Certificate	1SAA920000-0705
RoHS Information	1SAD938506-0302

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	92 mm
Package Level 1 Height	69.5 mm
Package Level 1 Depth / Length	57 mm
Package Level 1 Gross Weight	0.405 kg
Package Level 1 EAN	4013614525575
Package Level 2 Units	40 piece
Package Level 2 Width	280 mm
Package Level 2 Height	210 mm
Package Level 2 Depth / Length	395 mm
Package Level 2 Gross Weight	16.9 kg
Package Level 2 EAN	4013614539978

Classifications

Object Classification Code	Q
ETIM 5	EC001653 - Installation contactor for distribution board
ETIM 6	EC001653 - Installation contactor for distribution board
ETIM 7	EC001653 - Installation contactor for distribution board
eClass	V11.0 : 27142308
UNSPSC	39121529
IDEA Granular Category Code (IGCC)	4759 >> Installation contactor for distribution board

Categories

Low Voltage Products and Systems → Control Products → Contactors → Installation Contactors

Low Voltage Products and Systems → Modular DIN Rail Products → Command and Signalling devices → Installation Contactors

