

PRODUCT-DETAILS

CK-11

CK-11 Short Circuit Signaling Contact



General Information

Extended Product Type	CK-11
Product ID	1SAM101943R0001
EAN	4013614371073
Catalog Description	CK-11 Short Circuit Signaling Contact
Long Description	CK-11 Short-circuit signal contact

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85369095

Popular Downloads

Data Sheet, Technical Information	1SBC100173C0201
Instructions and Manuals	2CDC131089M6801

Dimensions

Product Net Width	9 mm
Product Net Height	92 mm
Product Net Depth /	73.5 mm

Length

Product Net Weight	0.035 kg
--------------------	----------

Technical

Terminal Type	Screw Terminals
Rated Operational Voltage	600 V AC 400 V DC Main Circuit 400 V AC
Rated Operational Current AC-15 (I_e)	(24 V) 6 A (120 V) 6 A (240 V) 4 A (380 / 400 V) 3 A
Rated Operational Current DC-13 (I_e)	(24 V) 2 A (125 V) 0.55 A (250 V) 0.27 A (400 V) 0.15 A
Rated Frequency (f)	Auxiliary Circuit 50 Hz Auxiliary Circuit 60 Hz Auxiliary Circuit DC
Rated Impulse Withstand Voltage (U_{imp})	Auxiliary Circuit 6 kV
Rated Insulation Voltage (U_i)	690 V
Degree of Protection	IP20
Connecting Capacity Auxiliary Circuit	Flexible with Ferrule 1/2x 0.75 ... 1.5 mm ² Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 2x 0.75 mm ² Flexible 1/2x 0.75 ... 1 mm ² Rigid 1/2x 1.0 ... 2.5 mm ²
Tightening Torque	Auxiliary Circuit 0.8 ... 1.0 N·m
Wire Stripping Length	Auxiliary Circuit 8 mm
Recommended Screw Driver	Pozidriv 2
Number of Auxiliary Contacts NO	1
Number of Auxiliary Contacts NC	1
Standards	IEC/EN 60947-1 IEC/EN 60947-4-1 IEC/EN 60947-5-1 UL 60947-1 UL 60947-4-1
Product Name	Short Circuit Signaling Contact
Suitable For	MS325 MO325
Suitable for Product Class	Manual Motor Starter
Accessory Group	Electrical
Accessory Type	Short Circuit Signaling Contact

Technical UL/CSA

Contact Rating UL/CSA	B300 B600 Q300
-----------------------	----------------------

Environmental

Ambient Air Temperature	Operation -25 ... +50 °C Storage -50 ... +80 °C
RoHS Status	Following EU Directive 2011/65/EU

Certificates and Declarations (Document Number)

CQC Certificate	CQC2011010304508192
cUL Certificate	1SAA918002-1701
Declaration of Conformity - CCC	2020980305001263
Declaration of Conformity - CE	1SAD938517-0003 1SAD938510-0037
Declaration of Conformity - UKCA	1SAD938500-1003
GOST Certificate	1SAA918000-2703
Instructions and Manuals	2CDC131089M6801
RoHS Information	1SAD938514-0003
UL Certificate	1SAA918002-1601

Container Information

Package Level 1 Width	210 mm
Package Level 1 Depth / Length	79 mm
Package Level 1 Height	105 mm
Package Level 1 Gross Weight	0.43 kg
Package Level 1 EAN	4013614442384
Package Level 1 Units	10 piece

Classifications

Object Classification Code	Q
ETIM 4	EC002498 - Accessories for low-voltage switch technology
ETIM 5	EC000041 - Auxiliary contact block
ETIM 6	EC000041 - Auxiliary contact block
ETIM 7	EC000041 - Auxiliary contact block
eClass	V11.0 : 27371302
UNSPSC	39121522
IDEA Granular Category Code (IGCC)	4742 >> Electrical contacts

Categories

Low Voltage Products and Systems → Control Products → Manual Motor Starters → Manual Motor Starters Accessories

