

## PRODUCT-DETAILS

# MS132-16-HKF1-11

## MS132-16-HKF1-11 Manual Motor Starter



### General Information

|                       |                                       |
|-----------------------|---------------------------------------|
| Extended Product Type | MS132-16-HKF1-11                      |
| Product ID            | 1SAM350005R1011                       |
| EAN                   | 4013614404511                         |
| Catalog Description   | MS132-16-HKF1-11 Manual Motor Starter |

|                  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
|------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Long Description | <p>The MS132-16-HKF1-11 manual motor starter (also known as motor protection circuit breaker or manual motor protector) is a compact 45 mm width device with a rated operational current of <math>I_e = 16.0</math> A and a pre-assembled front mounted auxiliary contact HKF1-11. This device is used to manually switch on and off motors and to protect them reliably and without the need for a fuse from short-circuits, overload and phase failures. The manual motor starter offers a rated service short-circuit breaking capacity <math>I_{cs} = 100</math> kA at 400 VAC and trip class 10. Further features are the build-in disconnect function, temperature compensation, trip-free mechanism and a rotary handle with a clear switch position indication. The manual motor starter is suitable for three- and single-phase applications. The handle is lockable to protect against unauthorized changes. Auxiliary contacts, signaling contacts, undervoltage releases, shunt trips, 3-phase bus bars, power in-feed blocks and terminal spacers are available as accessory.</p> |
|------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

### Ordering

|                        |          |
|------------------------|----------|
| Minimum Order Quantity | 1 piece  |
| Customs Tariff Number  | 85362010 |

### Popular Downloads

|                       |                 |
|-----------------------|-----------------|
| Data Sheet, Technical | 2CDC131021D0202 |
|-----------------------|-----------------|

## Information

|                                   |                                    |
|-----------------------------------|------------------------------------|
| Instructions and Manuals          | 2CDC131022M6802                    |
| Instructions and Manuals (Part 2) | 2CDC131060M0202                    |
| Time-Current Characteristic Curve | 1SAM300505F0011                    |
| I <sup>2</sup> t Characteristic   | 1SAM300507F0001<br>1SAM300507F0003 |
| Cut-off Current Characteristic    | 1SAM300508F0001<br>1SAM300508F0003 |
| Dimension Diagram                 | 1SAM300402F0002                    |

## Dimensions

|                            |          |
|----------------------------|----------|
| Product Net Width          | 45 mm    |
| Product Net Height         | 97.8 mm  |
| Product Net Depth / Length | 86.55 mm |
| Product Net Weight         | 0.326 kg |

## Technical

|                                                                     |                                                                                                                                         |
|---------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| Rated Service Short-Circuit Breaking Capacity (I <sub>cs</sub> )    | (230 V AC) 100 kA<br>(250 V DC) 3 Poles in Series 10 kA<br>(400 V AC) 100 kA<br>(440 V AC) 30 kA<br>(500 V AC) 20 kA<br>(690 V AC) 3 kA |
| Rated Ultimate Short-Circuit Breaking Capacity (I <sub>cu</sub> )   | (230 V AC) 100 kA<br>(400 V AC) 100 kA<br>(440 V AC) 30 kA<br>(500 V AC) 20 kA<br>(690 V AC) 3 kA                                       |
| Rated Instantaneous Short-Circuit Current Setting (I <sub>i</sub> ) | 240 A                                                                                                                                   |
| Setting Range                                                       | 10 ... 16 A                                                                                                                             |
| Rated Operational Power AC-3 (P <sub>e</sub> )                      | (400 V) Three Phase 7.5 kW                                                                                                              |
| Rated Operational Power AC-3e (P <sub>e</sub> )                     | (400 V) Three Phase 7.5 kW                                                                                                              |
| Rated Operational Voltage                                           | Main Circuit 690 V AC<br>Main Circuit 250 V DC                                                                                          |
| Rated Operational Current (I <sub>e</sub> )                         | 16 A                                                                                                                                    |
| Rated Operational Current AC-3 (I <sub>e</sub> )                    | 16 A                                                                                                                                    |
| Rated Operational Current AC-3e (I <sub>e</sub> )                   | 16 A                                                                                                                                    |
| Rated Operational Current DC-5 (I <sub>e</sub> )                    | 16 A                                                                                                                                    |
| Rated Frequency (f)                                                 | Main Circuit 50 Hz<br>Main Circuit 60 Hz                                                                                                |
| Rated Impulse Withstand Voltage (U <sub>imp</sub> )                 | Main Circuit 6 kV                                                                                                                       |
| Rated Insulation Voltage (U <sub>i</sub> )                          | 690 V                                                                                                                                   |
| Power Loss                                                          | at Rated Operating Conditions per Pole 1.1 W                                                                                            |
| Number of Poles                                                     | 3                                                                                                                                       |
| Mounted Auxiliary Contacts                                          | 1 NO, 1 NC                                                                                                                              |

|                                                          |                                                                                                                                                                                                                                                                                                |
|----------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Conventional Free-air Thermal Current (I <sub>th</sub> ) | Main Circuit 16 A                                                                                                                                                                                                                                                                              |
| Degree of Protection                                     | Housing IP20<br>Main Circuit Terminals IP10                                                                                                                                                                                                                                                    |
| Pollution Degree                                         | 3                                                                                                                                                                                                                                                                                              |
| Electrical Durability                                    | 50000 cycle                                                                                                                                                                                                                                                                                    |
| Mechanical Durability                                    | 100000 cycle                                                                                                                                                                                                                                                                                   |
| Terminal Type                                            | Screw Terminals                                                                                                                                                                                                                                                                                |
| Connecting Capacity Main Circuit                         | Flexible with Ferrule 1/2x 0.75 ... 6 mm <sup>2</sup><br>Flexible with Insulated Ferrule 1/2x 0.75 ... 6 mm <sup>2</sup><br>Flexible 1/2x 1 ... 2.5 mm <sup>2</sup><br>Flexible 1/2x 2.5 ... 6 mm <sup>2</sup><br>Rigid 1/2x 1 ... 2.5 mm <sup>2</sup><br>Rigid 1/2x 2.5 ... 6 mm <sup>2</sup> |
| Connecting Capacity Auxiliary Circuit                    | Flexible with Ferrule 1/2x 0.75 ... 1.5 mm <sup>2</sup><br>Flexible with Insulated Ferrule 1/2x 0.75 ... 1.5 mm <sup>2</sup><br>Flexible 1/2x 0.75 ... 1.5 mm <sup>2</sup><br>Rigid 1/2x 1 ... 1.5 mm <sup>2</sup>                                                                             |
| Tightening Torque                                        | Auxiliary Circuit 0.8 ... 1.2 N·m<br>Main Circuit 2 N·m                                                                                                                                                                                                                                        |
| Wire Stripping Length                                    | Auxiliary Circuit 8 mm<br>Main Circuit 10 mm                                                                                                                                                                                                                                                   |
| Recommended Screw Driver                                 | Pozidriv 2                                                                                                                                                                                                                                                                                     |
| Mounting Position                                        | Position 1 to 6                                                                                                                                                                                                                                                                                |
| Mounting on DIN Rail                                     | TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715<br>TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715                                                                                                                                                                                 |
| Minimum Mounting Distance                                | Electrical Conductive Board, Horizontal - Up to 400 V 0 mm<br>Electrical Conductive Board, Horizontal - Up to 690 V 1.5 mm<br>Electrical Conductive Board, Vertical 75 mm<br>Other Device Same Type, Horizontal 0 mm<br>Other Device Same Type, Vertical 150 mm                                |
| Actuator Type                                            | Rotary Handle                                                                                                                                                                                                                                                                                  |
| Contact Position Indication                              | ON / OFF / TRIP                                                                                                                                                                                                                                                                                |
| Standards                                                | IEC/EN 60947-1<br>IEC/EN 60947-2<br>IEC/EN 60947-4-1<br>IEC/EN 60947-5-1<br>UL 60947-1<br>UL 60947-4-1                                                                                                                                                                                         |
| Remarks                                                  | UL508 Self-Protected Combination Motor Controller (Type E) in combination with feeder block S1-M3-xx                                                                                                                                                                                           |

## Technical UL/CSA

|                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|-------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Short-Circuit Current Rating (SCCR) | Manual Self-Protected Combination Controllers (Type E), (480Y / 277 V AC) 30 kA<br>Any UL Listed Fuses or Circuit-Breakers, Group Installations (480 V AC) 35 kA<br>Any UL Listed Fuses or Circuit-Breakers, Group Installations (600 V AC) 35 kA<br>Any UL Listed Fuses or Circuit-Breakers, Motor Disconnect (480 V AC) 30 kA<br>Any UL Listed Fuses or Circuit-Breakers, Motor Disconnect (600 V AC) 18 kA<br>Any UL Listed Fuses or Circuit-Breakers, Tap Conductor Protection in Group Installations (480Y / 277 V AC) 30 kA<br>Any UL Listed Fuses or Circuit-Breakers, Tap Conductor Protection in Group Installations (600Y / 347 V AC) 18 kA |
| Maximum Operating Voltage UL/CSA    | Auxiliary Circuit 250 V AC/DC<br>Main Circuit 600 V AC                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Ampere Rating UL/CSA                | 16 A                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Horsepower Rating UL/CSA            | (200 V AC) Three Phase 3 Hp<br>(208 V AC) Three Phase 3 Hp<br>(220 ... 240 V AC) Three Phase 5 Hp<br>(440 ... 480 V AC) Three Phase 10 Hp                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |

|                                                 |                                                                                                                                                                                     |
|-------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                                 | (550 ... 600 V AC) Three Phase 10 Hp                                                                                                                                                |
| Full Load Amps Motor Use                        | (200 V AC) Three Phase 11 A<br>(208 V AC) Three Phase 10.6 A<br>(220 ... 240 V AC) Three Phase 15.2 A<br>(440 ... 480 V AC) Three Phase 14 A<br>(550 ... 600 V AC) Three Phase 11 A |
| Locked Rotor Amps                               | (200 V AC) Three Phase 73.6 A<br>(208 V AC) Three Phase 71 A<br>(220 ... 240 V AC) Three Phase 92 A<br>(440 ... 480 V AC) Three Phase 81 A<br>(550 ... 600 V AC) Three Phase 64.8 A |
| General Use Rating<br>UL/CSA                    | (600 V AC) 16 A                                                                                                                                                                     |
| Connecting Capacity<br>Main Circuit UL/CSA      | Flexible 1/2x 16-8 AWG<br>Stranded 1/2x 16-8 AWG                                                                                                                                    |
| Connecting Capacity<br>Auxiliary Circuit UL/CSA | Flexible 1/2x 16-14 AWG<br>Stranded 1/2x 16-14 AWG                                                                                                                                  |
| Tightening Torque<br>UL/CSA                     | Auxiliary Circuit 7 in-lb<br>Main Circuit 18 in-lb                                                                                                                                  |
| Contact Rating UL/CSA                           | B300<br>R300                                                                                                                                                                        |

## Environmental

|                                                |                                                                                                                                 |
|------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| Ambient Air Temperature                        | Around the Enclosure 0 ... +40 °C<br>Operation -25 ... +70 °C<br>Operation Compensated -25 ... +60 °C<br>Storage -50 ... +80 °C |
| Ambient Air Temperature Compensation           | Yes                                                                                                                             |
| Maximum Operating Altitude Permissible         | 2000 m                                                                                                                          |
| Resistance to Shock acc. to IEC 60068-2-27     | 11 ms Pulse 25g                                                                                                                 |
| Resistance to Vibrations acc. to IEC 60068-2-6 | 5g / 3 ... 150 Hz                                                                                                               |
| RoHS Status                                    | Following EU Directive 2011/65/EU                                                                                               |

## Certificates and Declarations (Document Number)

|                                 |                                    |
|---------------------------------|------------------------------------|
| ABS Certificate                 | 1SAA963001-0101                    |
| ATEX Certificate                | 1SAA963000-3901                    |
| BV Certificate                  | 1SAA963001-0201                    |
| CB Certificate                  | 1SAA963002-2002                    |
| CQC Certificate                 | CQC2017010307034621                |
| cUL Certificate                 | UL_E137861<br>UL_E345003           |
| cULus Certificate               | cUL_E137861                        |
| Cut-off Current Characteristic  | 1SAM300508F0001<br>1SAM300508F0003 |
| Declaration of Conformity - CCC | 2020980307004600                   |
| Declaration of Conformity - CE  | 1SAD938516-0125                    |
| DNV Certificate                 | 1SAA963001-0303                    |
| EAC Certificate                 | 1SAA963000-2701                    |
| GL Certificate                  | 1SAA963001-0401                    |
| GOST Certificate                | 1SAA963001-2702                    |
| I <sup>2</sup> t Characteristic | 1SAM300507F0001<br>1SAM300507F0003 |
| Instructions and Manuals        | 2CDC131022M6802                    |

|                                   |                          |
|-----------------------------------|--------------------------|
| Instructions and Manuals (Part 2) | 2CDC131060M0202          |
| KC Certificate                    | 1SAA963002-1502          |
| LR Certificate                    | 1SAA963001-0502          |
| RINA Certificate                  | 1SAA963002-0802          |
| RMRS Certificate                  | 1SAA918000-0704          |
| RoHS Information                  | 1SAD938511-0125          |
| Time-Current Characteristic Curve | 1SAM300505F0011          |
| UL Certificate                    | UL_E137861<br>UL_E345003 |

## Container Information

|                                |                 |
|--------------------------------|-----------------|
| Package Level 1 Units          | box 1 piece     |
| Package Level 1 Width          | 92 mm           |
| Package Level 1 Depth / Length | 102 mm          |
| Package Level 1 Height         | 50 mm           |
| Package Level 1 Gross Weight   | 0.341 kg        |
| Package Level 1 EAN            | 4013614404511   |
| Package Level 2 Units          | carton 40 piece |
| Package Level 2 Width          | 280 mm          |
| Package Level 2 Depth / Length | 395 mm          |
| Package Level 2 Height         | 210 mm          |
| Package Level 2 Gross Weight   | 14.026 kg       |
| Package Level 2 EAN            | 4013614409165   |

## Classifications

|                                    |                                                         |
|------------------------------------|---------------------------------------------------------|
| Object Classification Code         | F                                                       |
| ETIM 4                             | EC000074 - Motor protective circuit-breaker             |
| ETIM 5                             | EC000074 - Motor protective circuit-breaker             |
| ETIM 6                             | EC000074 - Motor protection circuit-breaker             |
| ETIM 7                             | EC000074 - Motor protection circuit-breaker             |
| eClass                             | V11.0 : 27370401                                        |
| UNSPSC                             | 39121521                                                |
| IDEA Granular Category Code (IGCC) | 4845 >> 3 Pole Motor Circuit Protector Circuit Breakers |
| E-Number (Finland)                 | 3705910                                                 |

## Accessories

| Identifier      | Description                | Type     | Quantity | Unit Of Measure |
|-----------------|----------------------------|----------|----------|-----------------|
| 1SAM201901R1001 | HKF1-11 Auxiliary Contact  | HKF1-11  | 1        | piece           |
| 1SAM201901R1201 | HKF1-11K Auxiliary Contact | HKF1-11K | 1        | piece           |
| 1SAM201901R1002 | HKF1-20 Auxiliary Contact  | HKF1-20  | 1        | piece           |
| 1SAM201901R1202 | HKF1-20K Auxiliary Contact | HKF1-20K | 1        | piece           |
| 1SAM201901R1004 | HKF1-01 Auxiliary Contact  | HKF1-01  | 1        | piece           |
| 1SAM201901R1003 | HKF1-10 Auxiliary Contact  | HKF1-10  | 1        | piece           |
| 1SAM201902R1002 | HK1-20 Auxiliary Contact   | HK1-20   | 1        | piece           |
| 1SAM201902R1202 | HK1-20K Auxiliary Contact  | HK1-20K  | 1        | piece           |
| 1SAM201902R1001 | HK1-11 Auxiliary Contact   | HK1-11   | 1        | piece           |

|                 |                                        |             |   |       |
|-----------------|----------------------------------------|-------------|---|-------|
| 1SAM201902R1201 | HK1-11K Auxiliary Contact              | HK1-11K     | 1 | piece |
| 1SAM201902R1003 | HK1-02 Auxiliary Contact               | HK1-02      | 1 | piece |
| 1SAM201902R1203 | HK1-02K Auxiliary Contact              | HK1-02K     | 1 | piece |
| 1SAM201902R1004 | HK1-20L Auxiliary Contact              | HK1-20L     | 1 | piece |
| 1SAM201902R1204 | HK1-20LK Auxiliary Contact             | HK1-20LK    | 1 | piece |
| 1SAM201903R1002 | SK1-20 Signal Contact                  | SK1-20      | 1 | piece |
| 1SAM201903R1202 | SK1-20K Signal Contact                 | SK1-20K     | 1 | piece |
| 1SAM201903R1001 | SK1-11 Signal Contact                  | SK1-11      | 1 | piece |
| 1SAM201903R1201 | SK1-11K Signal Contact                 | SK1-11K     | 1 | piece |
| 1SAM201903R1003 | SK1-02 Signal Contact                  | SK1-02      | 1 | piece |
| 1SAM201903R1203 | SK1-02K Signal Contact                 | SK1-02K     | 1 | piece |
| 1SAM301901R1002 | CK1-20 Short Circuit Signaling Contact | CK1-20      | 1 | piece |
| 1SAM301901R1001 | CK1-11 Short Circuit Signaling Contact | CK1-11      | 1 | piece |
| 1SAM301901R1003 | CK1-02 Short Circuit Signaling Contact | CK1-02      | 1 | piece |
| 1SAM201910R1001 | AA1-24 Shunt Trip                      | AA1-24      | 1 | piece |
| 1SAM201910R1002 | AA1-110 Shunt Trip                     | AA1-110     | 1 | piece |
| 1SAM201910R1003 | AA1-230 Shunt Trip                     | AA1-230     | 1 | piece |
| 1SAM201910R1004 | AA1-400 Shunt Trip                     | AA1-400     | 1 | piece |
| 1SAM201904R1010 | UA1-20 Undervoltage Release            | UA1-20      | 1 | piece |
| 1SAM201904R1001 | UA1-24 Undervoltage Release            | UA1-24      | 1 | piece |
| 1SAM201904R1002 | UA1-48 Undervoltage Release            | UA1-48      | 1 | piece |
| 1SAM201904R1003 | UA1-60 Undervoltage Release            | UA1-60      | 1 | piece |
| 1SAM201904R1004 | UA1-110 Undervoltage Release           | UA1-110     | 1 | piece |
| 1SAM201904R1008 | UA1-208 Undervoltage Release           | UA1-208     | 1 | piece |
| 1SAM201904R1005 | UA1-230 Undervoltage Release           | UA1-230     | 1 | piece |
| 1SAM201904R1006 | UA1-400 Undervoltage Release           | UA1-400     | 1 | piece |
| 1SAM201904R1007 | UA1-415 Undervoltage Release           | UA1-415     | 1 | piece |
| 1SAM201904R1009 | UA1-575 Undervoltage Release           | UA1-575     | 1 | piece |
| 1SAM201906R1102 | PS1-2-0-65 Busbar                      | PS1-2-0-65  | 1 | piece |
| 1SAM201906R1112 | PS1-2-1-65 Busbar                      | PS1-2-1-65  | 1 | piece |
| 1SAM201906R1122 | PS1-2-2-65 Busbar                      | PS1-2-2-65  | 1 | piece |
| 1SAM201916R1103 | PS1-3-0-100 Busbar                     | PS1-3-0-100 | 1 | piece |
| 1SAM201906R1103 | PS1-3-0-65 Busbar                      | PS1-3-0-65  | 1 | piece |
| 1SAM201916R1113 | PS1-3-1-100 Busbar                     | PS1-3-1-100 | 1 | piece |
| 1SAM201906R1113 | PS1-3-1-65 Busbar                      | PS1-3-1-65  | 1 | piece |
| 1SAM201916R1123 | PS1-3-2-100 Busbar                     | PS1-3-2-100 | 1 | piece |
| 1SAM201906R1123 | PS1-3-2-65 Busbar                      | PS1-3-2-65  | 1 | piece |
| 1SAM201916R1104 | PS1-4-0-100 Busbar                     | PS1-4-0-100 | 1 | piece |
| 1SAM201906R1104 | PS1-4-0-65 Busbar                      | PS1-4-0-65  | 1 | piece |
| 1SAM201916R1114 | PS1-4-1-100 Busbar                     | PS1-4-1-100 | 1 | piece |
| 1SAM201906R1114 | PS1-4-1-65 Busbar                      | PS1-4-1-65  | 1 | piece |
| 1SAM201906R1124 | PS1-4-2-65 Busbar                      | PS1-4-2-65  | 1 | piece |
| 1SAM201916R1105 | PS1-5-0-100 Busbar                     | PS1-5-0-100 | 1 | piece |
| 1SAM201906R1105 | PS1-5-0-65 Busbar                      | PS1-5-0-65  | 1 | piece |
| 1SAM201916R1115 | PS1-5-1-100 Busbar                     | PS1-5-1-100 | 1 | piece |
| 1SAM201906R1115 | PS1-5-1-65 Busbar                      | PS1-5-1-65  | 1 | piece |
| 1SAM201906R1125 | PS1-5-2-65 Busbar                      | PS1-5-2-65  | 1 | piece |
| 1SAM201907R1101 | S1-M1-25 Power Infeed Block            | S1-M1-25    | 1 | piece |
| 1SAM201907R1102 | S1-M2-25 Power Infeed Block            | S1-M2-25    | 1 | piece |
| 1SAM201907R1103 | S1-M3-25 Power Infeed Block            | S1-M3-25    | 1 | piece |
| 1SAM201913R1103 | S1-M3-35 Power Infeed Block            | S1-M3-35    | 1 | piece |
| 1SAM201914R1002 | S1-PB1-25 Power Infeed Block           | S1-PB1-25   | 1 | piece |
| 1SAM301911R1001 | TS1-M3-S1 Terminal Spacer              | TS1-M3-S1   | 1 | piece |
| 1SAM301912R1001 | TS1-M3-S2 Terminal Spacer              | S1-M3-S2    | 1 | piece |
| 1SAM201908R1001 | BS1-3 Protection Cover                 | BS1-3       | 1 | piece |
| 1SAM201909R1001 | FS116 Screw Fixing Kit                 | FS116       | 1 | piece |
| 1SAM201914R1001 | PB1-1-32 Connecting Link               | PB1-1-32    | 1 | piece |

|                 |                                           |          |   |       |
|-----------------|-------------------------------------------|----------|---|-------|
| GJF1101903R0002 | SA2 - Terminals and Installation Material | SA2      | 1 | piece |
| 1SAM201911R1012 | IB132-F Enclosure                         | IB132-F  | 1 | piece |
| 1SAM201911R1010 | IB132-G Enclosure                         | IB132-G  | 1 | piece |
| 1SAM201911R1011 | IB132-Y Enclosure                         | IB132-Y  | 1 | piece |
| 1SAM201912R1010 | DMS132-G Door Mounting Kit                | DMS132-G | 1 | piece |
| 1SAM201912R1011 | DMS132-Y Door Mounting Kit                | DMS132-Y | 1 | piece |
| 1SAM201909R1021 | MSAH1 Shaft Supporter                     | MSAH1    | 1 | piece |
| 1SAM201920R1011 | MSHD-LTB Handles                          | MSHD-LTB | 1 | piece |
| 1SAM201920R1012 | MSHD-LTY Handles                          | MSHD-LTY | 1 | piece |
| 1SAM101923R0002 | MSMN Driver                               | MSMN     | 1 | piece |
| 1SAM101923R0012 | MSMNO Driver                              | MSMNO    | 1 | piece |
| 1SCA101647R1001 | OXS6X85 SHAFT                             | OXS6X85  | 1 | piece |
| 1SCA108043R1001 | OXS6X105 SHAFT                            | OXS6X105 | 1 | piece |
| 1SCA101655R1001 | OXS6X130 SHAFT                            | OXS6X130 | 1 | piece |
| 1SCA101659R1001 | OXS6X180 SHAFT                            | OXS6X180 | 1 | piece |

Categories

Low Voltage Products and Systems → Circuit Breakers → Manual Motor Starters

Low Voltage Products and Systems → Control Products → Manual Motor Starters → Manual Motor Starters

