

PRODUCT-DETAILS

DRAF16-11S 24-60V50/60HZ

DRAF16-11S 24-60V50/60HZ DRAF16-11S



General Information

Extended Product Type	DRAF16-11S 24-60V50/60HZ
Product ID	1SBK174237R1100
EAN	3471522144416
Catalog Description	DRAF16-11S 24-60V50/60HZ DRAF16-11S
Long Description	DRAF16-11S 24-60V50/60HZ enclosed Direct-On-Line starter with AF contactors

Ordering

EAN	3471522144416
Minimum Order Quantity	1 piece
Customs Tariff Number	85364900

Dimensions

Product Net Width	107 mm
Product Net Height	230 mm
Product Net Depth / Length	131 mm
Product Net Weight	0.82 kg

Container Information

Package Level 1 Units	box 1 piece
-----------------------	-------------

Package Level 1 Width	243 mm
Package Level 1 Height	143 mm
Package Level 1 Depth / Length	112 mm
Package Level 1 Gross Weight	0.82 kg
Package Level 1 EAN	3471522144416

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Additional Information

Degree of Protection	acc. to IEC 60529, IEC 60947-1, EN 60529 Auxiliary Terminals IP66
Enclosure Class	4x
Housing Material	ABS
Number of Auxiliary Contacts NC	0
Number of Auxiliary Contacts NO	1
Number of Main Contacts NC	0
Number of Main Contacts NO	3
Order Multiple	1 piece
Product Main Type	DRAF16
Product Name	DRAF16-11S
Rated Operational Current AC-1 (I _e)	(690 V) 40 °C 30
Rated Operational Current AC-3 (I _e)	(380 / 400 V) 60 °C 18 A
Rated Operational Power AC-3 (P _e)	(380 / 400 V) 7.5 kW
RoHS Date	20171115

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	1SBC100199C0201
Declaration of Conformity - CE	1SBD250009U1000
Instructions and Manuals	1SBC101048M6801
RoHS Information	1SBD250009U1000
UL Certificate	UL_20150729-E312527-16-1
UL Listing Card	UL_E312527

Classifications

ETIM 4	EC000200 - Enclosure for control circuit devices
ETIM 5	EC000200 - Enclosure for control circuit devices
ETIM 6	EC000200 - Enclosure for control circuit devices
ETIM 7	EC000200 - Enclosure for control circuit devices
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Control Products → Contactor Starters → Enclosed Starters

