

## PRODUCT-DETAILS

# AFS09Z-30-22-30

## AFS09Z-30-22-30 24VDC Contactor



### General Information

|                       |                                 |
|-----------------------|---------------------------------|
| Extended Product Type | AFS09Z-30-22-30                 |
| Product ID            | 1SBL136082R3022                 |
| EAN                   | 3471523158191                   |
| Catalog Description   | AFS09Z-30-22-30 24VDC Contactor |

### Long Description

AFS09Z ... AFS38Z contactors are designed for machine safety applications. They are delivered with fixed front-mounted auxiliary contact blocks making them ideal for monitoring and controlling circuits. Mechanically linked and mirror contacts make your system safer.

- control circuit with electronic coil interface: - dedicated 24 V DC for direct control by PLC-output  $\geq 250$  mA, low holding consumption up to 1.7 W - reduced panel energy consumption
- mirror and mechanically linked contacts, with front marked symbol acc. to IEC60947-5-1, always guaranteeing the right contactor status - front-mounted auxiliary contact block: - permanently fixed - protective cover to prevent manual operation - yellow housing for easy identification - minimum switching capacity 12 V / 3 mA, with a failure rate 10<sup>-7</sup> acc. to IEC 60947-5-4 - built-in surge suppression

### Ordering

|                        |          |
|------------------------|----------|
| Minimum Order Quantity | 1 piece  |
| Customs Tariff Number  | 85364900 |

### Popular Downloads

|                          |                 |
|--------------------------|-----------------|
| Instructions and Manuals | 1SBC101052M6801 |
|--------------------------|-----------------|

## Dimensions

|                            |          |
|----------------------------|----------|
| Product Net Width          | 45 mm    |
| Product Net Depth / Length | 130.5 mm |
| Product Net Height         | 86 mm    |
| Product Net Weight         | 0.49 kg  |

## Technical

|                                                    |                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|----------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Number of Main Contacts NO                         | 3                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Number of Main Contacts NC                         | 0                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Number of Auxiliary Contacts NO                    | 2                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Number of Auxiliary Contacts NC                    | 2                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Standards                                          | IEC 60947-1 / 60947-4-1 and EN 60947-1 / 60947-4-1, UL 508, CSA C22.2 N° 14                                                                                                                                                                                                                                                                                                                                                                          |
| Rated Operational Voltage                          | Auxiliary Circuit 690 V<br>Main Circuit 690 V                                                                                                                                                                                                                                                                                                                                                                                                        |
| Rated Frequency (f)                                | Auxiliary Circuit 50 / 60 Hz<br>Main Circuit 50 / 60 Hz                                                                                                                                                                                                                                                                                                                                                                                              |
| Conventional Free-air Thermal Current ( $I_{th}$ ) | acc. to IEC 60947-4-1, Open Contactors $q = 40^\circ\text{C}$ 35 A<br>acc. to IEC 60947-5-1, $q = 40^\circ\text{C}$ 16 A                                                                                                                                                                                                                                                                                                                             |
| Rated Operational Current AC-1 ( $I_e$ )           | (690 V) $40^\circ\text{C}$ 25 A<br>(690 V) $60^\circ\text{C}$ 25 A<br>(690 V) $70^\circ\text{C}$ 22 A                                                                                                                                                                                                                                                                                                                                                |
| Rated Operational Current AC-3 ( $I_e$ )           | (415 V) $60^\circ\text{C}$ 9 A<br>(440 V) $60^\circ\text{C}$ 9 A<br>(500 V) $60^\circ\text{C}$ 9.5 A<br>(690 V) $60^\circ\text{C}$ 7 A<br>(380 / 400 V) $60^\circ\text{C}$ 9 A<br>(220 / 230 / 240 V) $60^\circ\text{C}$ 9 A                                                                                                                                                                                                                         |
| Rated Operational Power AC-3 ( $P_e$ )             | (400 V) 4 kW<br>(415 V) 4 kW<br>(440 V) 4 kW<br>(500 V) 5.5 kW<br>(690 V) 5.5 kW<br>(380 / 400 V) 4 kW<br>(220 / 230 / 240 V) 2.2 kW                                                                                                                                                                                                                                                                                                                 |
| Rated Operational Current AC-15 ( $I_e$ )          | (500 V) 2 A<br>(690 V) 2 A<br>(24 / 127 V) 6 A<br>(220 / 240 V) 4 A<br>(400 / 440 V) 3 A                                                                                                                                                                                                                                                                                                                                                             |
| Rated Short-time Withstand Current ( $I_{cw}$ )    | at $40^\circ\text{C}$ Ambient Temp, in Free Air, from a Cold State 10 s 150 A<br>at $40^\circ\text{C}$ Ambient Temp, in Free Air, from a Cold State 15 min 35 A<br>at $40^\circ\text{C}$ Ambient Temp, in Free Air, from a Cold State 1 min 60 A<br>at $40^\circ\text{C}$ Ambient Temp, in Free Air, from a Cold State 1 s 300 A<br>at $40^\circ\text{C}$ Ambient Temp, in Free Air, from a Cold State 30 s 80 A<br>for 0.1 s 140 A<br>for 1 s 100 A |
| Maximum Breaking Capacity                          | $\cos \phi = 0.45$ ( $\cos \phi = 0.35$ for $I_e > 100$ A) at 440 V 250 A<br>$\cos \phi = 0.45$ ( $\cos \phi = 0.35$ for $I_e > 100$ A) at 690 V 106 A                                                                                                                                                                                                                                                                                               |
| Maximum Electrical Switching Frequency             | (AC-1) 600 cycles per hour<br>(AC-15) 1200 cycles per hour<br>(AC-2 / AC-4) 300 cycles per hour<br>(AC-3) 1200 cycles per hour<br>(DC-13) 900 cycles per hour                                                                                                                                                                                                                                                                                        |
| Rated Operational Current DC-13 ( $I_e$ )          | (24 V) 6 A / 144 W<br>(48 V) 2.8 A / 134 W<br>(72 V) 1 A / 72 W<br>(110 V) 0.55 A / 60 W<br>(125 V) 0.55 A / 69 W<br>(220 V) 0.27 A / 60 W<br>(250 V) 0.27 A / 68 W<br>(400 V) 0.15 A / 60 W<br>(500 V) 0.13 A / 65 W                                                                                                                                                                                                                                |

|                                                        |                                                                                                                                                                                                                                                                        |
|--------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                                        | (600 V) 0.1 A / 60 W                                                                                                                                                                                                                                                   |
| Rated Insulation Voltage<br>(U <sub>i</sub> )          | acc. to IEC 60947-4-1 and VDE 0110 (Gr. C) 690 V<br>acc. to UL/CSA 600 V                                                                                                                                                                                               |
| Rated Impulse Withstand<br>Voltage (U <sub>imp</sub> ) | 6 kV                                                                                                                                                                                                                                                                   |
| Maximum Mechanical<br>Switching Frequency              | 3600 cycles per hour                                                                                                                                                                                                                                                   |
| Rated Control Circuit<br>Voltage (U <sub>c</sub> )     | 50 Hz -<br>50 Hz / 60 Hz 100 ... 250 V<br>60 Hz -<br>DC Operation 24 V                                                                                                                                                                                                 |
| Operate Time                                           | Between Coil De-energization and NC Contact Closing 22 ... 57 ms<br>Between Coil De-energization and NO Contact Opening 17 ... 29 ms<br>Between Coil Energization and NC Contact Opening 20 ... 35 ms<br>Between Coil Energization and NO Contact Closing 27 ... 53 ms |
| Connecting Capacity Main<br>Circuit                    | Flexible with Ferrule 1/2x 0.75 ... 6 mm <sup>2</sup><br>Flexible with Insulated Ferrule 1x 0.75 ... 4 mm <sup>2</sup><br>Flexible with Insulated Ferrule 2x 0.75 ... 2.5 mm <sup>2</sup><br>Rigid 1/2x 1 ... 6 mm <sup>2</sup>                                        |
| Connecting Capacity<br>Auxiliary Circuit               | Flexible with Ferrule 1/2x 0.75 ... 2.5 mm <sup>2</sup><br>Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm <sup>2</sup><br>Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm <sup>2</sup><br>Rigid 1/2x 1 ... 2.5 mm <sup>2</sup>                                  |
| Connecting Capacity<br>Control Circuit                 | Flexible with Ferrule 1/2x 0.75 ... 2.5 mm <sup>2</sup><br>Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm <sup>2</sup><br>Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm <sup>2</sup><br>Rigid 1/2x 1 ... 2.5 mm <sup>2</sup>                                  |
| Wire Stripping Length                                  | Auxiliary Circuit 10 mm<br>Control Circuit 10 mm<br>Main Circuit 10 mm                                                                                                                                                                                                 |
| Degree of Protection                                   | acc. to IEC 60529, IEC 60947-1, EN 60529 Auxiliary Terminals IP40<br>acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20<br>acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20                                                                      |
| Terminal Type                                          | Screw Terminals                                                                                                                                                                                                                                                        |

## Technical UL/CSA

|                              |                                                                                                                                                           |
|------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------|
| General Use Rating<br>UL/CSA | (600 V AC) 25 A                                                                                                                                           |
| Horsepower Rating<br>UL/CSA  | (220 ... 240 V AC) Three Phase 2 hp<br>(240 V AC) Single Phase 1-1/2 hp<br>(440 ... 480 V AC) Three Phase 5 hp<br>(550 ... 600 V AC) Three Phase 7-1/2 hp |
| Tightening Torque<br>UL/CSA  | Auxiliary Circuit 11 lA<br>Control Circuit 11 lA<br>Main Circuit 13 lA                                                                                    |

## Environmental

|                                                   |                                                                                                                                                                                           |
|---------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Ambient Air Temperature                           | Close to Contactor Fitted with Thermal O/L Relay -25 ... +60 °C<br>Close to Contactor without Thermal O/L Relay -40 ... +70 °C<br>Close to Contactor for Storage -60 ... +80 °C           |
| Climatic Withstand                                | Category B according to IEC 60947-1 Annex Q                                                                                                                                               |
| Maximum Operating<br>Altitude Permissible         | 3000 m                                                                                                                                                                                    |
| Resistance to Vibrations<br>acc. to IEC 60068-2-6 | 5 ... 300 Hz 4 g closed position / 2 g open position                                                                                                                                      |
| Resistance to Shock acc.<br>to IEC 60068-2-27     | Closed, Shock Direction: A 30 K40<br>Closed, Shock Direction: B1 25 K40<br>Closed, Shock Direction: B2 15 K40<br>Closed, Shock Direction: C1 25 K40<br>Closed, Shock Direction: C2 25 K40 |
| RoHS Status                                       | Following EU Directive 2011/65/EU                                                                                                                                                         |

## Certificates and Declarations (Document Number)

|                                    |                         |
|------------------------------------|-------------------------|
| CB Certificate                     | CB_SE-96551             |
| CCC Certificate                    | CCC_2010010304445624    |
| CQC Certificate                    | CQC2010010304445624     |
| cUL Certificate                    | UL_20180227_E312527_7_1 |
| Declaration of Conformity<br>- CCC | 2020980304001253        |
| Declaration of Conformity<br>- CE  | 1SBD250022U1000         |
| DNV Certificate                    | DNV-GL_TAE00001AF-3     |
| DNV GL Certificate                 | DNV-GL_TAE00001AF-3     |
| EAC Certificate                    | EAC_RUC-FRME77B03199    |
| GL Certificate                     | DNV-GL_TAE00001AF-3     |
| Instructions and Manuals           | 1SBC101052M6801         |
| RINA Certificate                   | RINA_ELE240318XG        |
| RMRS Certificate                   | RMRS_1802705280         |
| RoHS Information                   | 1SBD250022U1000         |
| UL Listing Card                    | E312527                 |

## Container Information

|                                   |                |
|-----------------------------------|----------------|
| Package Level 1 Units             | box 1 piece    |
| Package Level 1 Width             | 96 mm          |
| Package Level 1 Depth /<br>Length | 145 mm         |
| Package Level 1 Height            | 50 mm          |
| Package Level 1 Gross<br>Weight   | 0.54 kg        |
| Package Level 1 EAN               | 3471523158191  |
| Package Level 2 Units             | crate 12 piece |
| Package Level 2 Width             | 51 mm          |
| Package Level 2 Depth /<br>Length | 98 mm          |
| Package Level 2 Height            | 148 mm         |
| Package Level 2 Gross<br>Weight   | 6.48 kg        |
| Package Level 3 Units             | 576 piece      |

## Classifications

|                            |                                           |
|----------------------------|-------------------------------------------|
| Object Classification Code | Q                                         |
| ETIM 4                     | EC000066 - Magnet contactor, AC-switching |
| ETIM 5                     | EC000066 - Magnet contactor, AC-switching |
| ETIM 6                     | EC000066 - Power contactor, AC switching  |
| ETIM 7                     | EC000066 - Power contactor, AC switching  |
| eClass                     | V11.0 : 27371003                          |
| UNSPSC                     | 39121529                                  |
| E-Number (Finland)         | 3708045                                   |
| E-Number (Sweden)          | 3210677                                   |

---

## Categories

---

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors

