

PRODUCT-DETAILS

TAL26-40-00 25-45V DC

TAL26-40-00 25-45V DC Contactor



General Information

Extended Product Type	TAL26-40-00 25-45V DC
Product ID	1SBL243261R5200
EAN	3471522321527
Catalog Description	TAL26-40-00 25-45V DC Contactor

Long Description

TAL26 4-pole contactors are mainly used for controlling non-inductive or slightly inductive loads (i.e. resistance furnaces...) and generally for controlling power circuits up to 690 V AC and 440 V DC. The contactors can also be used for many other applications such lighting... The TAL... series 4-pole contactors are of the block type design. - Main poles and auxiliary contact blocks: 4 N.O. main poles, front and side-mounted add-on auxiliary contact blocks - Control circuit: DC operated with solid core magnet circuit. The polarity on the coil terminals (A1+ and A2-) must be respected - Accessories: a wide range of accessories is available. TAL... contactors are fitted with low consumption DC coils and offer a large coil voltage range.

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85364900

Popular Downloads

Data Sheet, Technical Information	1SNC001003C0202
Instructions and Manuals	1SBC101007M5501
Dimension Diagram	FPTE307866

Dimensions

Product Net Width	54 mm
Product Net Depth / Length	110.6 mm
Product Net Height	90 mm
Product Net Weight	0.75 kg

Technical

Number of Main Contacts NO	4
Number of Main Contacts NC	0
Number of Auxiliary Contacts NO	0
Number of Auxiliary Contacts NC	0
Rated Operational Voltage	Main Circuit 690 V
Conventional Free-air Thermal Current (I_{th})	acc. to IEC 60947-4-1, Open Contactors $q = 40^\circ\text{C}$ 45 A
Rated Operational Current AC-1 (I_e)	(690 V) 40°C 45 (690 V) 55°C 40 (690 V) 70°C 32
Rated Operational Current AC-3 (I_e)	(415 V) 55°C 26 A (440 V) 55°C 26 A (500 V) 55°C 22 A (690 V) 55°C 13 A (380 / 400 V) 55°C 26 A (220 / 230 / 240 V) 55°C 26
Rated Operational Power AC-3 (P_e)	(380 / 400 V) 11 kW
Rated Breaking Capacity AC-3 acc. to IEC 60947-4-1	8 x I_e AC-3
Rated Making Capacity AC-3 acc. to IEC 60947-4-1	10 x I_e AC-3
Short-Circuit Protective Devices	gG Type Fuses 50 A
Maximum Breaking Capacity	$\cos \phi = 0.45$ ($\cos \phi = 0.35$ for $I_e > 100$ A) at 440 V 420 A $\cos \phi = 0.45$ ($\cos \phi = 0.35$ for $I_e > 100$ A) at 690 V 106 A
Maximum Electrical Switching Frequency	(AC-1) 600 cycles per hour (AC-2 / AC-4) 300 cycles per hour (AC-3) 1200 cycles per hour
Rated Insulation Voltage (U_i)	acc. to IEC 60947-4-1 and VDE 0110 (Gr. C) 1000 V acc. to UL/CSA 600 V
Rated Impulse Withstand Voltage (U_{imp})	8 kV
Mechanical Durability	10 million
Maximum Mechanical Switching Frequency	3600 cycles per hour
Rated Control Circuit Voltage (U_c)	DC Operation 25 ... 45 V
Coil Consumption	Holding DC (U_{min} / U_{max}) 2.7 / 9 W Pull-in DC (U_{min} / U_{max}) 2.7 / 9 W
Operate Time	Between Coil De-energization and NO Contact Opening 12 ... 18 ms Between Coil Energization and NO Contact Closing 55 ... 110 ms
Connecting Capacity Main Circuit	Flexible with Cable End 0.75 ... 4 mm ² Rigid Cable 1.5 ... 6 mm ²
Connecting Capacity	Flexible with Cable End 0.75 ... 2.5 mm ²

Auxiliary Circuit	Rigid Cable 1 ... 4 mm ²
Degree of Protection	acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20
Connecting Terminals (delivered in open position) Main Poles	M 4 (+,-) pozidriv 2 screw with cable clamp
Terminal Type	Screw Terminals

Environmental

Ambient Air Temperature	Close to Contactor for Storage -60 ... +80 °C Near Contactor for Operation in Free Air -40 ... +55 °C
Climatic Withstand	acc. to IEC 60068-2-30 and 60068-2-11 - UTE C 63-100 specification II
Maximum Operating Altitude Permissible	3000 m
Resistance to Shock acc. to IEC 60068-2-27	Closed, Shock Direction: A 20 K40 Closed, Shock Direction: B1 15 K40 Closed, Shock Direction: C1 20 K40 Closed, Shock Direction: C2 14 K40 Open, Shock Direction: A 10 K40 Open, Shock Direction: B1 5 K40 Open, Shock Direction: C1 8 K40 Open, Shock Direction: C2 8 K40 Shock Direction: B2 10 K40
RoHS Status	Following EU Directive 2011/65/EU

Certificates and Declarations (Document Number)

CCC Certificate	CCC_2004010304112231
CQC Certificate	CQC2004010304112231
CSA Certificate	CSA_1033838_LR056745
Declaration of Conformity - CCC	2020980304001611
Declaration of Conformity - CE	1SBD250804U1000
EAC Certificate	EAC_RU C-FR ME77 B01010
Environmental Information	1SBD250122E1002
GOST Certificate	GOST_POCCFRME77B07175
Instructions and Manuals	1SBC101007M5501
RoHS Information	1SBD250804U1000

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	100 mm
Package Level 1 Depth / Length	134 mm
Package Level 1 Height	62 mm
Package Level 1 Gross Weight	0.75 kg
Package Level 1 EAN	3471522321527
Package Level 2 Units	box 20 piece
Package Level 2 Width	300 mm
Package Level 2 Depth / Length	245 mm
Package Level 2 Height	308 mm
Package Level 2 Gross Weight	15 kg
Package Level 3 Units	384 piece

Classifications		
Object Classification Code		Q
ETIM 4	EC000066 - Magnet contactor, AC-switching	
ETIM 5	EC000066 - Magnet contactor, AC-switching	
ETIM 6	EC000066 - Power contactor, AC switching	
ETIM 7	EC000066 - Power contactor, AC switching	
UNSPSC		39121529

Categories
Low Voltage Products and Systems → Control Products → Contactors → Block Contactors

