

## PRODUCT-DETAILS

UA63-30-00RA 220-230V 50Hz / 230-240V  
60Hz

UA63-30-00RA 220-230V 50Hz / 230-240V  
60Hz Contactor



### General Information

|                       |                                                      |
|-----------------------|------------------------------------------------------|
| Extended Product Type | UA63-30-00RA 220-230V 50Hz / 230-240V 60Hz           |
| Product ID            | 1SBL371024R8000                                      |
| EAN                   | 3471522304803                                        |
| Catalog Description   | UA63-30-00RA 220-230V 50Hz / 230-240V 60Hz Contactor |

### Long Description

UA63..RA 3-pole contactors for capacitor switching, can be used in installations in which the peak current far exceeds 100 times nominal rms current. The contactors are delivered complete with their damping resistors and must be used without additional inductances (see table below). The capacitors must be discharged (maximum residual voltage at terminals  $\leq 50$  V) before being re-energized when the contactors are making. Their electrical durability is 250 000 operating cycles for  $U_e < 500$  V and 100 000 operating cycles for  $500 \text{ V} \leq U_e \leq 690$  V. The UA..RA contactors are fitted with a special front mounted block, which ensures the serial insertion of 3 damping resistors into the circuit to limit the current peak on energization of the capacitor bank. Their connection also ensures capacitor precharging in order to limit the second current peak occurring upon making of the main poles. The insertion of resistors allows to damp the highest current peak of the capacitor when switching on, whatever its level. The UA..RA series 3-pole contactors are of the block type design. - Main poles: 3 main poles - Control circuit: AC operated with laminated magnet circuit - Accessories: a wide range of accessories is available.

### Ordering

|                        |          |
|------------------------|----------|
| Minimum Order Quantity | 1 piece  |
| Customs Tariff Number  | 85364900 |

## Popular Downloads

|                                   |                 |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 1SBC101140C0203 |
| Instructions and Manuals          | 1SBC101002M5501 |
| Dimension Diagram                 | FPTE307844      |

## Dimensions

|                            |          |
|----------------------------|----------|
| Product Net Width          | 70 mm    |
| Product Net Depth / Length | 140.4 mm |
| Product Net Height         | 150 mm   |
| Product Net Weight         | 1.35 kg  |

## Technical

|                                          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Number of Main Contacts NO               | 3                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Number of Main Contacts NC               | 0                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Number of Auxiliary Contacts NO          | 0                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Number of Auxiliary Contacts NC          | 0                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Rated Operational Voltage                | Main Circuit 690 V                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Rated Operational Current AC-3 ( $I_e$ ) | (1000 V) 55 °C 25 A<br>(220 / 230 / 240 V) 55 °C 65 A<br>(380 / 400 V) 55 °C 65 A<br>(415 V) 55 °C 65 A<br>(440 V) 55 °C 65 A<br>(500 V) 55 °C 55 A<br>(690 V) 55 °C 43 A                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Rated Operational Power AC-3 ( $P_e$ )   | (220 / 230 / 240 V) 18.5 KWT<br>(380 / 400 V) 30 KWT<br>(415 V) 37 KWT<br>(440 V) 37 KWT<br>(500 V) 37 KWT<br>(690 V) 37 KWT                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Rated Operational Power AC-6b ( $P_e$ )  | (230 / 240 V) 40 °C, 50 / 60 Hz 30 kvar<br>(230 / 240 V) 55 °C, 50 / 60 Hz 27 kvar<br>(230 / 240 V) 70 °C, 50 / 60 Hz 23 kvar<br>(400 / 415 V) 40 °C, 50 / 60 Hz 50 kvar<br>(400 / 415 V) 70 °C, 50 / 60 Hz 39 kvar<br>(400 / 415 V) 55 °C, 50 / 60 Hz 45 kvar<br>(440 V) 40 °C, 50 / 60 Hz 55 kvar<br>(440 V) 55 °C, 50 / 60 Hz 48 kvar<br>(440 V) 70 °C, 50 / 60 Hz 42.5 kvar<br>(500 / 550 V), 40 °C, 50 / 60 Hz 65 kvar<br>(500 / 550 V) 55 °C, 50 / 60 Hz 60 kvar<br>(500 / 550 V) 70 °C, 50 / 60 Hz 50 kvar<br>(690 V) 40 °C, 50 / 60 Hz 80 kvar<br>(690 V) 55 °C, 50 / 60 Hz 75 kvar<br>(690 V) 70 °C, 50 / 60 Hz 65 kvar |
| Short-Circuit Protective Devices         | gG Type Fuses 200 A                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Maximum Breaking Capacity                | cos phi=0.45 (cos phi=0.35 for $I_e > 100$ A) at 440 V 1300 A<br>cos phi=0.45 (cos phi=0.35 for $I_e > 100$ A) at 690 V 630 A                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Maximum Electrical                       | 240 cycles per hour                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |

## Switching Frequency

|                                                                    |                                                                                                                                                                                                               |
|--------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Rated Insulation Voltage<br>(U <sub>i</sub> )                      | acc. to IEC 60947-4-1 and VDE 0110 (Gr. C) 1000 V<br>acc. to UL/CSA 600 V                                                                                                                                     |
| Rated Impulse Withstand<br>Voltage (U <sub>imp</sub> )             | 8 kV                                                                                                                                                                                                          |
| Rated Control Circuit<br>Voltage (U <sub>c</sub> )                 | 50 Hz 220 ... 230 V<br>60 Hz 230 ... 240 V                                                                                                                                                                    |
| Coil Consumption                                                   | Average Holding Value 50 / 60 Hz 18 5.5 V·A<br>Average Holding Value 50 Hz 18 5.5 V·A<br>Average Holding Value 60 Hz 18 5.5 V·A<br>Average Pull-in Value 50 Hz 180 V·A<br>Average Pull-in Value 60 Hz 210 V·A |
| Operate Time                                                       | Between Coil De-energization and NO Contact Opening 4 ... 11 ms<br>Between Coil Energization and NO Contact Closing 8 ... 27 ms                                                                               |
| Connecting Capacity Main<br>Circuit                                | Flexible with Cable End 6 ... 10 mm <sup>2</sup><br>Rigid Cable 6 ... 16 mm <sup>2</sup>                                                                                                                      |
| Connecting Capacity<br>Auxiliary Circuit                           | Flexible with Cable End 0.75 ... 2.5 mm <sup>2</sup><br>Rigid Cable 1 ... 4 mm <sup>2</sup>                                                                                                                   |
| Degree of Protection                                               | acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20                                                                                                                                                  |
| Connecting Terminals<br>(delivered in open<br>position) Main Poles | M 6 (+,-) pozidriv 2 screws with 1x (13 x 10 mm) connector                                                                                                                                                    |
| Terminal Type                                                      | Screw Terminals                                                                                                                                                                                               |

## Environmental

|                                           |                                                                                                                                                                                                                      |
|-------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Ambient Air Temperature                   | Close to Contactor for Storage -60 ... +80 °C<br>Near Contactor for Operation in Free Air (0.85 ... 1.1 U <sub>c</sub> ) -40 ... +55 °C<br>Near Contactor for Operation in Free Air (U <sub>c</sub> ) -40 ... +70 °C |
| Climatic Withstand                        | acc. to IEC 60068-2-30 and 60068-2-11 - UTE C 63-100 specification II                                                                                                                                                |
| Maximum Operating<br>Altitude Permissible | 3000 m                                                                                                                                                                                                               |
| RoHS Status                               | Following EU Directive 2011/65/EU                                                                                                                                                                                    |

## Certificates and Declarations (Document Number)

|                                    |                                                                   |
|------------------------------------|-------------------------------------------------------------------|
| CB Certificate                     | CB_CN45331                                                        |
| CCC Certificate                    | CCC_2018010304128277                                              |
| CQC Certificate                    | CQC2018010304128277<br>CQC2018010304128276<br>CQC2008010304290409 |
| CSA Certificate                    | CSA_1033838_LR056745                                              |
| Declaration of Conformity<br>- CCC | 2020980304001620<br>2020980304001623<br>2020980304001215          |
| Declaration of Conformity<br>- CE  | 1SBD250805U1000                                                   |
| Environmental Information          | 1SBD250124E1000                                                   |
| GOST Certificate                   | GOST_POCCFRME77B07175                                             |
| Instructions and Manuals           | 1SBC101002M5501                                                   |
| RoHS Information                   | 1SBD250805U1000                                                   |
| UL Certificate                     | UL_20120830-E312527-10-1                                          |
| UL Listing Card                    | UL_E312527                                                        |

## Container Information

|                                |               |
|--------------------------------|---------------|
| Package Level 1 Units          | box 1 piece   |
| Package Level 1 Width          | 160 mm        |
| Package Level 1 Depth / Length | 200 mm        |
| Package Level 1 Height         | 85 mm         |
| Package Level 1 Gross Weight   | 1.35 kg       |
| Package Level 1 EAN            | 3471522304803 |
| Package Level 2 Units          | box 63 piece  |
| Package Level 2 Width          | 245 mm        |
| Package Level 2 Depth / Length | 75 mm         |
| Package Level 2 Height         | 153 mm        |
| Package Level 2 Gross Weight   | 85.05 kg      |

## Classifications

|                            |                                       |
|----------------------------|---------------------------------------|
| Object Classification Code | Q                                     |
| ETIM 4                     | EC001079 - Capacitor magnet contactor |
| ETIM 5                     | EC001079 - Capacitor magnet contactor |
| ETIM 6                     | EC001079 - Capacitor contactor        |
| ETIM 7                     | EC001079 - Capacitor contactor        |
| eClass                     | V11.0 : 27371006                      |
| UNSPSC                     | 39121529                              |
| E-Number (Finland)         | 3709167                               |

## Categories

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors → UA and UA..RA Contactors

