

PRODUCT-DETAILS

CC5-01

CC5-01 Auxiliary Contact Block



General Information

Extended Product Type	CC5-01
Product ID	1SBN010011R1001
EAN	3471522121035
Catalog Description	CC5-01 Auxiliary Contact Block
Long Description	CC5-01 Auxiliary Contact Block

Ordering

E-Number (Finland)	3709236
EAN	3471522121035
Minimum Order Quantity	10 piece
Customs Tariff Number	85389099

Dimensions

Product Net Width	11 mm
Product Net Height	47 mm
Product Net Depth / Length	32.5 mm
Product Net Weight	0.014 kg

Container Information

Package Level 1 Units	box 10 piece
Package Level 1 Width	65 mm
Package Level 1 Height	40 mm
Package Level 1 Depth / Length	129.5 mm
Package Level 1 Gross Weight	0.14 kg
Package Level 1 EAN	3471522121035
Package Level 2 Units	box 270 piece
Package Level 2 Width	300 mm
Package Level 2 Height	308 mm
Package Level 2 Depth / Length	245 mm
Package Level 2 Gross Weight	3.78 kg
Package Level 3 Units	9720 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Additional Information

Degree of Protection	acc. to IEC 60529, IEC 60947-1, EN 60529 Auxiliary Terminals IP40
Maximum Electrical Switching Frequency	1200 cycles per hour
Maximum Mechanical Switching Frequency	3600 cycles per hour
Mechanical Durability	10 million 3 million
Minimum Switching Capacity	A9 ... A75 17 / 5 VLT4K A95 ... A110 24 / 50 VLT4K
Mounting Position	Front face
Mounting Type	Front mounting
Number of Auxiliary Contacts NC	1
Number of Auxiliary Contacts NO	0
Order Multiple	10 piece
Power Loss	at Rated Operating Conditions per Pole 0.1 W
Product Main Type	Accessories for Block Contactors
Product Name	Auxiliary Contact Block
Rated Breaking Capacity acc. to IEC 60947-5-1	10 x I _e AC-15
Rated Frequency (f)	Supply Circuit 50 60 Hz
Rated Insulation Voltage (U _i)	acc. to IEC 60947-5-1 and VDE 0110 (Gr. C) 690 V acc. to UL/CSA 600 V
Rated Making Capacity acc. to IEC 60947-5-1	10 x I _e AC-15
Rated Operational Current AC-15 (I _e)	(500 V) 2 A (690 V) 2 A (24 / 127 V) 6 A (220 / 240 V) 4 A (380 / 400 V) 3 A
Rated Operational Current DC-13 (I _e)	(24 V) 6 / 144 A (48 V) 2.8 / 134 A (72 V) 1 / 72 A (125 V) 0.55 / 69 A (250 V) 0.3 / 75 A
Rated Operational Voltage	Auxiliary Circuit 690 V Main Circuit 24 V

Remarks	100
RoHS Date	20171115
Suitable For	A9
	A12
	A16
	A26
	A30
	A40
	A50
	A63
	A75
	A95
	A110
	AL9
	AL12
	AL16
	AL26
	AL30
	AL40
	AE45
	AE50
	AE63
	AE75
	TAL9
	TAL12
	TAL16
	TAL26
	TAL30
	TAL40
	AF45
	AF50
	AF63
	AF75
	AF95
	AF110
	TAE45
	TAE50
	TAE75
	N22E
	N31E
	N40E
	NL22E
	NL31E
	NL40E
	TNL22E
	TNL31E
	TNL40E
Terminal Type	Screw Terminals

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	1SBC100122C0202_Ch04
Declaration of Conformity - CE	1SBD250809U1000
EAC Certificate	EAC_RU C-FR ME77 B03391
Environmental Information	1SBD250198E1000
GOST Certificate	GOST_POCCFRME77B07175
Instructions and Manuals	1SBC101012M5501
RINA Certificate	RINA_ELE172319XG001
RoHS Information	1SBD250809U1000

Classifications

ETIM 4	EC002498 - Accessories for low-voltage switch technology
ETIM 5	EC002498 - Accessories for low-voltage switch technology

ETIM 6	EC000041 - Auxiliary contact block
ETIM 7	EC000041 - Auxiliary contact block
Object Classification Code	K
UNSPSC	39120000
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors Accessories

