

PRODUCT-DETAILS

CE5-10W2

CE5-10W2 Auxiliary Contact Block



General Information

Extended Product Type	CE5-10W2
Product ID	1SBN010018R1010
EAN	3471522199522
Catalog Description	CE5-10W2 Auxiliary Contact Block

Long Description	CE5 auxiliary contact blocks are used for the operation of auxiliary circuits and control circuits for severe industrial environments.
	Types of auxiliary contact blocks for front mounting:
	• CE5 1-pole block, instantaneous with N.O. contact or N.C. contact, available in 2 IP degrees
	-- CE5 D with built-in microswitch IP40, degree of protection (IP20 on terminals)
	-- CE5 W with built-in microswitch IP67, degree of protection (IP20 on terminals).
	The auxiliary contact blocks are equipped with screw type connecting terminals delivered open, protected against accidental direct contact and bear the corresponding function marking.

Ordering

EAN	3471522199522
Minimum Order Quantity	1 piece
Customs Tariff Number	85389099

Dimensions

Product Net Width	9.8 mm
Product Net Height	46.8 mm
Product Net Depth / Length	32.5 mm
Product Net Weight	0.02 kg

Container Information

Package Level 1 Units	blister 1 piece
Package Level 1 Width	100 mm
Package Level 1 Height	10 mm
Package Level 1 Depth / Length	100 mm
Package Level 1 Gross Weight	0.02 kg
Package Level 1 EAN	3471522199522
Package Level 2 Units	box 126 piece
Package Level 2 Width	245 mm
Package Level 2 Height	153 mm
Package Level 2 Depth / Length	75 mm
Package Level 2 Gross Weight	2.52 kg
Package Level 3 Units	4536 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Additional Information

Degree of Protection	acc. to IEC 60529, IEC 60947-1, EN 60529 Auxiliary Terminals IP66
Medium Description	CE5 Auxiliary Contact Block is used for the operation of auxiliary circuits and control circuits for severe industrial environments. This product is a front mounted instantaneous auxiliary contact block. CE5 is available in 1-pole (e.g: CE5-01... has 0 N.O. and 1 N.C.). Contacts have 2 IP protection degrees: IP40 "D" or IP67 "W", with built-in micro-switch. Terminals are IP20. Rated for 0,1A or 2A. The auxiliary contact block is equipped with IP20 screw type connecting terminals delivered open.
Mounting Type	Front mounting
Number of Auxiliary Contacts NC	0
Number of Auxiliary Contacts NO	1
Order Multiple	1 piece
Product Main Type	Accessories for Block Contactors
Product Name	Auxiliary Contact Block
Rated Operational Current AC-15 (I_e)	(24 / 127 V) 2 A (220 / 240 V) 2 A
RoHS Date	20171115

Suitable For

- AF09
- AF12
- AF16
- AF26
- AF30
- AF38
- AF40
- AF52
- AF65
- AF80
- AF96
- NF
- A9
- A12
- A16
- A26
- A30
- A40
- A50
- A63
- A75
- A95
- A110
- N
- NL
- AX06
- AX09
- AX12
- AX18
- AX25
- AX32
- AX40
- AX50
- AX65
- AX80

Terminal TypeScrew Terminals

Certificates and Declarations (Document Number)	
CB Certificate	CB_SE-94569
CCC Certificate	CCC_2011010304466171
CQC Certificate	CQC2011010304466171
Declaration of Conformity - CCC	2020980304001286
Declaration of Conformity - CE	1SBD250817U1000
EAC Certificate	EAC_RU C-FR ME77 B03391
Environmental Information	1SBD250199E1000
GOST Certificate	GOST_POCCFRME77B07175
Instructions and Manuals	1SBC101013M5501
RINA Certificate	RINA_ELE172319XG001
RoHS Information	1SBD250809U1000

Classifications	
ETIM 4	EC002498 - Accessories for low-voltage switch technology
ETIM 5	EC002498 - Accessories for low-voltage switch technology
ETIM 6	EC000041 - Auxiliary contact block
ETIM 7	EC000041 - Auxiliary contact block

Object Classification Code	K
UNSPSC	39120000
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.0 : 27371302

Categories

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors Accessories

