

PRODUCT-DETAILS

WA4-10

WA4-10 24VDC Mechanical Latching Unit



Ogólne informacje

Extended Product Type	WA4-10
ID Produktu	1ISBN040100R1010
Numer EAN	3471523131057
Opis katalogowy	WA4-10 24VDC Mechanical Latching Unit

Opis	The WA4 mechanical latching unit for AF09 ... AF96 contactors and NF contactor relays ensures that the contactor or contactor relay remains switched on even if there is a lack or a failure of voltage. Standard contactors can be easily converted into compact latched contactors. The WA4 block contains a mechanical latching device with electromagnetic impulse unlatching (AC or DC) or manual unlatching.
	Operation After closing, the contactor continues to be held in the closed position by the latching mechanism should the supply voltage fail at the contactor coil terminals. Contactor opening can be controlled: • electrically by an impulse (AC or DC) on the WA4 block coil (the coil is not designed to be permanently energized) • manually by pressing the pushbutton on the front face of the WA4 block.
	Mounting The WA4 block is clipped onto the front face of the 1-stack up two slots in central position (see fig. below). The two other slots may accept CA4 single pole auxiliary contacts (1 block on each side of the mechanical latch). Additional CAL4 can be fitted on the side of the contactor in respect to the total number of built-in or additional N.O. and N.C. auxiliary contacts as described in the accessory fitting details part of each contactor type.

Charakterystyka zamówienia

Numer EAN	3471523131057
-----------	---------------

Minimalna ilość zamówienia	1 sztuka
Kod taryfy celnej	85389099

Wymiary

Szerokość produktu netto	19.8 mm
Wysokość produktu netto	41 mm
Głębokość produktu netto	67.4 mm
Waga produktu netto	0.065 kg

Informacje o pakowaniu

Jednostka opakowania (poziom 1)	box 1 sztuka
Szerokość opakowania (poziom 1)	72 mm
Wysokość opakowania (poziom 1)	44 mm
Długość opakowania (poziom 1)	25 mm
Waga opakowania brutto (poziom 1)	0.08 kg
EAN opakowania (poziom 1)	3471523131057

Normy środowiskowe

Status RoHS	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Technical UL/CSA

Momenty dokrecajace UL/CSA	Obwód sterowania 11 IA
----------------------------	------------------------

Dodatkowe informacje

Dane montażowe-obwód sterowania	Elastyczny z tulejką 1/2x 0.75 ... 2.5 mm² Elastyczny z izolowaną tulejką 1x 0.75 ... 2.5 mm² Elastyczny z izolowaną tulejką 2x 0.75 ... 1.5 mm² Sztywny 1/2x 1 ... 2.5 mm²
---------------------------------	--

Opis rozszerzony	WA4 Mechanical Latching Unit is front-mounted on AF09 ... AF65 contactors and NF contactor relay. It ensures that they remain switched on, even if there is a lack or a failure of voltage. After closing, the contactor continues to be held in the closed position by the latching mechanism, should the supply voltage at the contactor coil terminals fail. Contactor opening can be controlled electrically by an impulse (AC or DC) on the WA4 block coil, or manually by pressing the pushbutton on the front face of the WA4 block. Speed up your project by selecting quickly the WA4 coil thanks to a wide range of control voltages from 24 to 500 V 50/60 Hz - DC (WA4-11, 12, 13, 14). And also by extending your 24 V DC control solutions with a direct PLC control by 24V DC 500 mA (WA4-10). Optimum interface: 25% less compact than other market solutions, interface relay already included for direct control by PLC 24 V DC 500 mA, let enough space on AF to fix front or side-mounted auxiliary contacts in addition. Optimize your logistic by reducing your stock and increasing your solution proposal: standard contactors can be easily converted into compact latched contactors.
------------------	--

Ilość	1 sztuka
Typ produktu	Accessories for Block Contactors
Nazwa produktu	Mechanical Latching Unit
Ograniczenie napięcia	DC Operation 24 V

cewki (U_c)

Data RoHS

20171115

Odpowiedni do

AF09
AF12
AF16
AF26
AF30
AF38
NF

Momenty dokrecające

Obwód sterowania 1.2 N·m

Długość odizolowania
przewodu

Obwód sterowania 10 mm

Certyfikaty i deklaracje (Numer dokumentu)

Certyfikat CB	CB_HU-002678
Certyfikat CCC	CCC_2018010303063035
Certyfikat CQC	CQC2018010303063035
Declaration of Conformity - CCC	2020980303000186
Deklaracja zgodności - CE	1SBD250020U1000
Certyfikat EAC	EAC_RU C-FR ME77 B02940
Informacje środowiskowe	1SBD250196E1000
Instrukcje i podręczniki	1SBC101046M6801
Dane RoHS	1SBD250020U1000
UL Certificate	UL_20160705-E312527
UL Listing Card	UL_E312527

Klasyfikacje

ETIM 4	EC002498 - Accessories for low-voltage switch technology
ETIM 5	EC002498 - Accessories for low-voltage switch technology
ETIM 6	EC002498 - Accessories for low-voltage switch technology
ETIM 7	EC002498 - Accessories for low-voltage switch technology
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Kategorie

Produkty niskiego napięcia i systemy → Aparatura sterownicza → Styczniki → Block Contactors Accessories

