

PRODUCT-DETAILS

RV5/50

RV5/50 Surge Suppressor



Ogólne informacje

Extended Product Type	RV5/50
ID Produktu	1SBN050010R1000
Numer EAN	3471522121325
Opis katalogowy	RV5/50 Surge Suppressor

Opis	RV5/50 is a varistor surge suppressor designed to reduce the maximum overvoltage peak value and to limit or even completely eliminate the high pre-damping voltage frequencies, when used with an AC operated conventional contactor for a rated control circuit voltage between 24 ... 50 V AC 50/60Hz or with a DC operated conventional contactor for a rated control circuit voltage between 24 ... 50 V DC. The operation of inductive circuits causes overvoltages, in particular on opening of the contactor coil. The electromagnetic energy stored in the coil during contactor closing is restored on opening in the form of surges, the slope and amplitude of which may rise to several kilovolts. A number of drawbacks are observed ranging from interference on the electronic devices to breakdown of insulators and even destruction of certain sensitive components. Note: A varistor is a resistor whose value decreases to a very large extent when a certain voltage is applied at its terminals. Advantages: - the surge suppressor is clipped onto the top or side part in regards with the contactor or contactor relay base design without change in device overall dimensions. - high energy absorption: good damping - Unpolarized system. Drawback: clipping as from the varistor operating voltage, thus voltage front up to this point.
------	---

Charakterystyka zamówienia

E-Number (Finland)	3709201
Numer EAN	3471522121325
Minimalna ilość zamówienia	2 sztuka

Kod taryfy celnej	85363030
ID produktu zamiennego	1SBN050400R1000

Wymiary

Szerokość produktu netto	30.25 mm
Wysokość produktu netto	10.5 mm
Głębokość produktu netto	32.4 mm
Waga produktu netto	0.015 kg

Informacje o pakowaniu

Jednostka opakowania (poziom 1)	blister 2 sztuka
Szerokość opakowania (poziom 1)	65 mm
Wysokość opakowania (poziom 1)	12 mm
Długość opakowania (poziom 1)	96 mm
Waga opakowania brutto (poziom 1)	0.03 kg
EAN opakowania (poziom 1)	3471522121325
Jednostka opakowania (poziom 2)	box 324 sztuka
Szerokość opakowania (poziom 2)	245 mm
Wysokość opakowania (poziom 2)	153 mm
Długość opakowania (poziom 2)	75 mm
Waga opakowania brutto (poziom 2)	4.86 kg

Normy środowiskowe

Temperatura powietrza otoczenia	Eksplotacja -20 ... +70 °C
Status RoHS	Zgodny z dyrektywą EU 2002/95/EC sierpień 18, 2005 i poprawkami

Dodatkowe informacje

Mounting on Contactors	A 9...A 75
Rodzaj montażu	Clipped onto the top or bottom part of the contactor or contactor relay
Ilość	2 sztuka
Typ produktu	Accessories for Block Contactors
Nazwa produktu	Surge Suppressor
Ograniczenie napięcia cewki (U _c)	50 Hz / 60 Hz 24 ... 50 V DC DC Operation 24 ... 50 V DC
Data RoHS	20060502
Odpowiedni do	AS09 AS12 AS16 ASL09 ASL12 ASL16 VAS09 VAS12

VAS16
 VASL09
 VASL12
 VASL16
 NS
 NSL
 AX06
 AX09
 AX12
 AX18
 AX25
 AX32
 AX40
 AX50
 AX65
 AX80
 AX95
 AX115
 AX150
 NX
 UA16
 UA26
 UA30
 UA50
 UA63
 UA75
 UA16RA
 UA26RA
 UA30RA
 UA50RA
 UA63RA
 UA75RA
 GA75
 GAE75

Informacje techniczne	SUPPRESSOR
Wersja	Varistor

Certyfikaty i deklaracje (Numer dokumentu)

Arkusz danych, informacja techniczna	1SBC100214C0201
Deklaracja zgodności - CE	1SBD250816U1000
Informacje środowiskowe	1SBD250137E1000
Certyfikat GOST	GOST_POCCFR.ME77.B07175.pdf
Instrukcje i podręczniki	1SBC101020M9701
Certyfikat RINA	RINA_ELE172319XG001
Dane RoHS	1SBD350059R1000
UL Certificate	UL_20120523-E312527_1_3
UL Listing Card	UL_E312527

Klasyfikacje

ETIM 4	EC002498 - Accessories for low-voltage switch technology
ETIM 5	EC002498 - Accessories for low-voltage switch technology
ETIM 6	EC002498 - Accessories for low-voltage switch technology
ETIM 7	EC002498 - Accessories for low-voltage switch technology
UNSPSC	39120000
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Kategorie

Produkty niskiego napięcia i systemy → Aparatura sterownicza → Styczniki → Block Contactors Accessories

