

PRODUCT-DETAILS

RC5-2/50

RC5-2/50 Surge Suppressor



Ogólne informacje

Extended Product Type	RC5-2/50
ID Produktu	1SBN050200R1000
Numer EAN	3471522121288
Opis katalogowy	RC5-2/50 Surge Suppressor

Opis	RC5-2/50 is a RC type surge suppressor designed to reduce the maximum overvoltage peak value and to limit or even completely eliminate the high pre-damping voltage frequencies, when used with an AC operated conventional contactor for a rated control circuit voltage between 24 ... 50 V AC 50/60Hz. The operation of inductive circuits causes overvoltages, in particular on opening of the contactor coil. The electromagnetic energy stored in the coil during contactor closing is restored on opening in the form of surges, the slope and amplitude of which may rise to several kilovolts. A number of drawbacks are observed ranging from interference on the electronic devices to breakdown of insulators and even destruction of certain sensitive components. Advantages: - the surge suppressor is clipped onto the top or side part in regards with the contactor or contactor relay base design without change in device overall dimensions. - very fast clipping: attenuation of steep fronts and thus of high frequencies. No operating delays.
------	--

Charakterystyka zamówienia

Numer EAN	3471522121288
Minimalna ilość zamówienia	2 sztuka
Kod taryfy celnej	85363030
ID produktu zamiennego	1SBN050410R1000

Wymiary

Szerokość produktu netto	30.25 mm
Wysokość produktu netto	10.5 mm
Głębokość produktu netto	32.4 mm
Waga produktu netto	0.012 kg

Informacje o pakowaniu

Jednostka opakowania (poziom 1)	blister 2 sztuka
Szerokość opakowania (poziom 1)	65 mm
Wysokość opakowania (poziom 1)	12 mm
Długość opakowania (poziom 1)	96 mm
Waga opakowania brutto (poziom 1)	0.03 kg
EAN opakowania (poziom 1)	3471522121288
Jednostka opakowania (poziom 2)	box 324 sztuka
Szerokość opakowania (poziom 2)	245 mm
Wysokość opakowania (poziom 2)	153 mm
Długość opakowania (poziom 2)	75 mm
Waga opakowania brutto (poziom 2)	4.86 kg
Jednostka opakowania (poziom 3)	1200 sztuka

Normy środowiskowe

Temperatura powietrza otoczenia	Eksploatacja -20 ... +70 °C
Status RoHS	Zgodny z dyrektywą EU 2002/95/EC sierpień 18, 2005 i poprawkami

Dodatkowe informacje

Rodzaj montażu	Clipped onto the top or bottom part of the contactor or contactor relay
Ilość	2 sztuka
Typ produktu	Accessories for Block Contactors
Nazwa produktu	Surge Suppressor
Ograniczenie napięcia cewki (U _c)	50 Hz / 60 Hz 24 ... 50 V AC
Data RoHS	20060502
Odpowiedni do	AX50, AX65, AX80, AX95, AX115, AX150, UA50, UA63, UA75, UA50RA, UA63RA, UA75RA, GA75
Wersja	RC type

Certyfikaty i deklaracje (Numer dokumentu)

cUL Certificate	UL_20120523-E312527_1_3
Arkusze danych, informacja	1SBC100214C0201

techniczna

Deklaracja zgodności - CE	1SBD250816U1000
Certyfikat GOST	GOST_POCCFR.ME77.B07175.pdf
Certyfikat RINA	RINA_ELE172319XG001
Dane RoHS	1SBD350059R1000
UL Listing Card	UL_E312527

Klasyfikacje

ETIM 4	EC002498 - Accessories for low-voltage switch technology
ETIM 5	EC002498 - Accessories for low-voltage switch technology
ETIM 6	EC002498 - Accessories for low-voltage switch technology
ETIM 7	EC002498 - Accessories for low-voltage switch technology
UNSPSC	39121610
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
IDEA Granular Category Code (IGCC)	4906 >> Surge suppressers

Kategorie

Produkty niskiego napięcia i systemy → Aparatura sterownicza → Styczniki → Block Contactors Accessories

