


PRODUCT-DETAILS

LS30P41B02

LS30P41B02 Limit Switch



General Information

Extended Product Type	LS30P41B02
Product ID	1SBV010241R1202
EAN	3471522007407
Catalog Description	LS30P41B02 Limit Switch
Long Description	LS30P41B02 is a 30 mm wide, standard Limit Switch made of fiber-glass reinforced UL -V0 material, with 2 mounting holes at the top, 1 Pg13.5 cable entry on the bottom, plastic roller lever (Ø18 mm) actuator and 2 N.C snap action (Zb type) contacts

Ordering

EAN	3471522007407
Minimum Order Quantity	10 piece
Customs Tariff Number	85364900

Dimensions

Product Net Width	30 mm
Product Net Height	106 mm
Product Net Depth / Length	45 mm
Product Net Weight	0.083 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	54 mm
Package Level 1 Height	118 mm
Package Level 1 Depth / Length	32 mm
Package Level 1 Gross Weight	0.097 kg
Package Level 1 EAN	3471522007407
Package Level 2 Units	1 piece
Package Level 2 Gross Weight	0.09 kg

Environmental

Ambient Air Temperature	Operation -25 ... +70 °C Storage -30 ... +80 °C
Resistance to Vibrations acc. to IEC 60068-2-6	25g (10 to 500 Hz) no change in position of contacts greater than 100 µs
Resistance to Shock acc. to IEC 60068-2-27	Half-sine Pulse for 11 ms, No Change in Contact Position 50 m/s ²
RoHS Status	Following EU Directive 2011/65/EU

Technical UL/CSA

Pilot Duty of Contact Elements acc. UL508	A600 Q600
Flammability According to UL94	V-0

Safety Information

B10d Value	30 Millions operations
------------	------------------------

Additional Information

Action Type of the Contact Element (acc. to IEC 60947-5-1)	Snap action contacts
Actuator Type	Ø 18 mm polyamide roller lever
Actuation Speed	acc. to IEC 60947-5-1 Max. 1.5 m/s acc. to IEC 60947-5-1 Min. 0 m/s
Actuation Torque	acc. to IEC 60947-5-1 Min. 0.1 N·m
Angular Head Adjustment	adjustable head every 90°
Angular Lever Adjustment	10° in 10°
Climatic Withstand	according to IEC 68-2-3 and salty mist according to IEC 68-2-11
Conventional Free-air Thermal Current (I _{th})	acc. to IEC 60947-5-1, q = 40 °C 10 A
Connecting Capacity	Bar AWG 20 ... AWG 14 mm ² Bar 0.5 ... 2.5 mm ²
Consistency (Measured over 1 Million Operations)	0.1 mm
Contact Element Form (acc. to IEC 60947-5-1)	Zb
Connecting Terminals (delivered in open position)	M3.5 (+,-) pozidriv 2 screw with cable clamp

Degree of Protection	acc. to IEC 60529 IP65
Electrical Shock Protection acc. to IEC 536	Double insulation - Class II
Maximum Electrical Switching Frequency	3600 cycles per hour (AC-15) 3600 cycles per hour (DC-13) 3600 cycles per hour
Mechanical Durability	0 cycle
Mounting by Screws (not supplied)	2 x M4 screws
Mounting Position	all positions are authorised
Movement to be Detected	30° Cam Translation Movement
Number of Auxiliary Contacts NC	2
Number and Type of Bottom Cable Glands	Pg 13,5 Cable Gland
Operating Head Shape	A shape acc. EN 50047
Order Multiple	1 piece
Positive Opening Operation Torque (Direct Opening Action)	Minimum Torque acc. to IEC 60947-5-1 0.32 N·m
Positive Opening Operation of NC Contact (s)	Yes
Product Main Type	LS30
Product Name	Limit Switch
Rated Frequency (f)	Supply Circuit 50 60 Hz
Rated Impulse Withstand Voltage (U _{imp})	6 kV
Rated Insulation Voltage (U _i)	acc. to IEC 60947-5-1 and VDE 0110 (Gr. C) 500 V acc. to UL/CSA 600 V
Rated Operational Current AC-15 (I _e)	(230 V AC) 3.1 A (400 V) NC 4 (24 V) 10 A (130 V) 5.5 A (240 V) 3 A
Rated Operational Current DC-13 (I _e)	(24 V) 6 A (110 V) 0.6 A (125 V) 0.55 A (250 V) 0.4 A
Resistance Between Contacts	25 E45
RoHS Date	20171115
Standards	IEC 60947-1, IEC 60947-5-1, EN 60947-1, EN 60947-5-1, UL 508 and CSA C22 -2 N°14
Terminal Marking	according to EN 50013

Certificates and Declarations (Document Number)

CQC Certificate	CQC2004010305127663
cUL Certificate	9AKK107991A7379
Data Sheet, Technical Information	1SBC141157C0202
Declaration of Conformity - CCC	2020980305001785
Declaration of Conformity - CE	1SBD250883U1000
Environmental Information	1SBD250083E1000
Instructions and Manuals	1SBC141157C0202
RoHS Information	1SBD250883U1000

Classifications		
ETIM 4	EC001829 - Position switch modular	
ETIM 5	EC001829 - Position switch modular	
ETIM 6	EC000030 - End switch	
ETIM 7	EC000030 - End switch	
Object Classification Code	B	
UNSPSC	39121500	
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)	

Categories

Low Voltage Products and Systems → Control Products → Sensors → Limit Switches

